**Generic Finite Element Model For Mechanically
Consistent Scaling Of Composite Beam-to-column
Joint With Welded Connection**

Saenboon Amorntipsakul

Section of Steel and Composite Steel Structures
Department of Structural Engineering
Faculty of Civil Engineering

Kassel – Germany
June 2013

This work has been accepted by the Faculty of Civil Engineering of the University of Kassel as dissertation for acquiring the academic degree of Doktor der Ingenieurwissenschaften (Dr.-Ing.).

1. Advisor: Prof. Dr.-Ing. Uwe E. Dorka, University of Kassel
2. Supervisor: Prof. Dr.-Ing. Ekkehart Fehling, University of Kassel
3. Committee: Prof. Dr.-Ing. habil. Friedel Hartmann, University of Kassel
4. Committee: Prof. Dr.-Ing. Werner Seim, University of Kassel

Dissertation zur Erlangung des akademischen Grades eines Doktors der Ingenieurwissenschaften (Dr.-Ing.) an der Universität Kassel, Fachbereich Bauingenieur- und Umweltingenieurwesen, Institut für konstruktiven Ingenieurbau (IKI), Fachgebiet Stahl- und Verbundbau

Tag der mündlichen Prüfung: 15.06.2011

Dedicated to my beloved Mom, Dad, Family and Friends

Acknowledgements

This dissertation could not be certainly finished without supports from these people.

First, I would like to thank my ‘Doktorvater’ Prof. Dr.-Ing. Uwe E. Dorka. I am extremely grateful for all guidance, knowledge and understanding. I also would like to thank Prof. Dr.-Ing. Ekkehart Fehling as my second supervisor as well as Prof. Dr.-Ing. habil. Friedel Hartmann and Prof. Dr.-Ing. Werner Seim as the members of my committee.

Appreciation is also extended to all committee and my colleagues at University of Kassel. Nasser Mohammad Khanlou, the first one, introduced me how to implement C++ program into my work.

Additionally, I would like to express my heartfelt thanks to Dr. rer. nat. Dejavuth Suwimonteerabuth (Remy OSK 117) for helping me to cope with L^AT_EX and for your friendship, Werapol Bejranonda (Nong Chai) for preparing a few drawings in AUTOCAD and Alongkorn Kiatmontri (Nong J) for scanning some figures for me.

And I never forget all encouragement and forever friendship from my Suankularb friends, Suanjam friends, Nong Nong at Suanjam, all Thai students in Kassel as well as Nakorn Muannamorn (Pi Nui). Thank you very much for staying with me on my hard days.

Lastly, I would like to thank my warmest family with all my heart. Without all of you I probably gave up. My beloved mom, you inspired me to fulfil my dream and gave me strength to go further. I hope that you can perceive my missing and my accomplishments somewhere. Dad, who gives me everything, you also deserve my gratitude. My elder brothers, Saenpol and Saenchai Amorntipsakul, you give me good advices. My elder sisters, Somjai and Somporn Amorntipsakul, I exactly do not know how to thank both of you for every supports, not only financial support, but also your precious consolation. You always give me love and care.

I will never forget the hardest time in my life. I really do not know and now I would like to know how a man with doctor title feels.

Kassel, 07.12.2009.

Saenboon Amorntipsakul (Bahn OSK 107, Intania 73, AIT 73)

Acknowledgements II

I ever wrote that I would like to know how a man with doctor title feels for the very last years because at that time I thought that I would finish my Ph.D. soon. But I was totally wrong. I had to wait and to brutally fight against many obstacles longer than I expected. Now, it comes to the end of my never-ending Ph.D. story which I will never forget for the rest of my life.

After my oral examination, I had to work hard and to fight against every obstacle for such a long time. Not only my health but also my broken heart that always discouraged me. What I have done was like I was running in a marathon competition. But it was worse in my case, because I felt like I was running in the darkness. I did not see any light during these last two years. What I have done is just keep going, though sometimes I had to crawl. For most of marathon runners, I am sure that they want to overcome something on their minds. But for me, it was not the reason. I tried to finish my Ph.D. very hard in every means but not for myself anymore. I determined to finish it because I want to dedicate it to all my beloved, my whole family and my good friends. For sure, without all of you I could never finish this great task.

Mom, although we were apart for many years and forever, you are still in my mind. I hope that you can hear me somewhere out there. You are my never-give-up idol and my motivation. Dad, Tua Hea, Yi Hea, Tua Jae, Ning, and J, I really do not know how I should write to express my gratitude to all of you. You always gave every support to me. I am very lucky to be a member of the best family. Boat Thirachai Dheravatnvong, although you never perceive, you are my inspiration. We just knew each other but it was great that we had a chance to spend a good time together in Germany, even though it was very short. Lastly, I would like to thank J, Pi Nui 100, Remy 117, Aj. Rat Berlin, Joy Nürnberg, Chai & Mod Kassel, Veit Bayer and Tal & David Berlin for every help. You always stand by me.

I really do not know what will happen next in my life. Now one thing that I realise is that I will use every knowledge and experience that I have gained from these hard days to help other people who are suffering in this grey world.

Kassel, 13.06.2013.

Saenboon Amorntipsakul (Bahn OSK 107, Intania 73, AIT 73)

Abstract

To study the behaviour of beam-to-column composite connection more sophisticated finite element models is required, since component model has some severe limitations. In this research a generic finite element model for composite beam-to-column joint with welded connections is developed using current state of the art local modelling. Applying mechanically consistent scaling method, it can provide the constitutive relationship for a plane rectangular macro element with beam-type boundaries. Then, this defined macro element, which preserves local behaviour and allows for the transfer of five independent states between local and global models, can be implemented in high-accuracy frame analysis with the possibility of limit state checks. In order that macro element for scaling method can be used in practical manner, a generic geometry program as a new idea proposed in this study is also developed for this finite element model. With generic programming a set of global geometric variables can be input to generate a specific instance of the connection without much effort. The proposed finite element local model is validated against testing results from the University of Kaiserslautern. Finally, two illustrative examples for applying this macro element approach are presented. In the first example how to obtain the constitutive relationships of macro element is demonstrated. With certain assumptions for typical composite frame the constitutive relationships can be represented by bilinear laws for the macro bending and shear states that are then coupled by a two-dimensional surface law with yield and failure surfaces. In second example a scaling concept that combines sophisticated local models with a frame analysis using a macro element approach is presented as a practical application of this numerical model.

Contents

1	Introduction	1
1.1	General	1
1.2	Beam-to-column connection	2
1.3	Types of connections	3
1.4	Behaviour of composite connections	6
1.5	Classification of composite connections	7
1.6	Failure modes observed in connection tests	8
1.7	Literature survey	9
1.7.1	Research in Germany	9
1.7.2	Research in the United Kingdom	13
1.7.3	Research in other countries	16
2	Component model method	23
3	State of the art FE models	29
3.1	Finite element model developed by Ahmed et al.	29
3.2	Finite element model developed by Leon et al.	31
4	Macro element approach for scaling	33
4.1	Macro elements for scaling	33
4.2	Scaling of plane beam-to-column connections	36
5	Motivation and objective	43
6	Numerical modelling	45
6.1	Generic geometry	45
6.2	Boundary conditions	48
6.3	Element types and material properties	49
6.3.1	Steel elements and weld elements	49
6.3.2	Concrete elements	51
6.3.3	Crack elements	51
6.4	Limit state	55
6.4.1	Global plastic limit state	55

6.4.2	Failure states	55
7	Validation	67
7.1	Tests at University of Kaiserslautern	67
7.2	Validation	70
8	Illustrative examples	73
8.1	Example 1: Development of a two-surface model	73
8.2	Example 2: Macro element in frame analysis	88
9	Summary and conclusions	93
	Bibliography	95

List of Figures

1.1	Composite construction in buildings	2
1.2	Typical composite connection	3
1.3	Practical types of connections	4
1.4	Types of beam-to-column connection	5
1.5	Characteristic joint properties	6
1.6	Non-linear moment-rotation behaviour of a joint and classification of composite connection EC3 and EC4	7
1.7	Observed failure modes for composite connections	10
1.8	Typical weld failure in a composite end plate connection	11
1.9	Complete end plate yielding	11
1.10	Combined bolt fracture and yielding of the end plate	12
1.11	Buckling of the beams compression flange and web	12
1.12	Model of a composite beam with composite connection	14
1.13	Four types of steel joints	15
1.14	Different components of the composite joint model	18
1.15	Mechanical models of joints	20
2.1	Forming of groups at the end plate connection for the Innsbruck component model	24
2.2	Innsbruck component model for steel and composite connections	25
2.3	Refined component model	26
2.4	Comparison of Innsbruck component model and Eurocode component model	26
3.1	Finite element model from [Ahmed et al., 1995]	30
3.2	Finite element model from [Leon et al., 1996]	32
4.1	Macro stresses and strains of a plane triangle, tetrahedron and plane quadrilateral	34
4.2	Orthogonal boundary states for a beam-type macro element with associated one-dimensional constitutive relationships	35
4.3	Possible modification of component model from Innsbruck component model to represent a plane beam-column connection as macro element with orthogonal boundary states: 2 normal, 2 bending and 1 shear state	37

4.4	Orthogonal boundary states for a beam-to-column connection region and definition of DOFs	39
4.5	Simplified surface model for a beam-to-column connection	40
6.1	Welded beam-to-column composite connection and its components	46
6.2	Finite element local model for virtual testing of composite joint with welded connection	46
6.3	Two instances of virtual specimen generated with the generic model	48
6.4	Restraints used in this study	49
6.5	Linearly distributed loads applied at both ends of the virtual specimen to represent the macro bending state	49
6.6	Horizontal linearly distributed loads with vertical loads applied at both ends of the virtual specimen to represent the macro shear state	50
6.7	Eight-node brick element in SLang	50
6.8	Mises kinematic hardening material law for brick elements representing steel components	51
6.9	Idealised load deformation behaviour of a reinforced concrete member in tension	52
6.10	Distribution of strains in the case of single and stabilized crack formation .	53
6.11	Constitutive law for spring elements representing cracked regions	54
6.12	Bilinear material law for crack elements	54
6.13	Yield point defined in this study	56
6.14	Local buckling of an I-section column [Trahair et al., 2008]	57
6.15	Effects of local buckling on the resistances of compression member	57
6.16	Post-buckling behaviour of thin plates [Trahair et al., 2008]	58
6.17	Ultimate strength of plates in compression [Trahair et al., 2008]	58
6.18	Simply supported plate under bending and shear	59
6.19	Buckling coefficient for pure bending	60
6.20	Buckling coefficient for pure shear	61
6.21	Buckling coefficient for plate element under compression	63
6.22	Fillet weld connection loaded eccentrically out-of-plane	64
6.23	Relationship between strain of reinforcement in a crack and mean strain of reinforcement	65
6.24	Standard two-surface model for concrete	65
7.1	Test specimen	68
7.2	Setup of the test series	69
7.3	Crack pattern at the end of the test with reinforcement ratio 0.4 percent .	69
7.4	Finite element local model for validation	70
7.5	Definition of rotation in the test	71
7.6	Deformed FE model	71
7.7	Bending moment–rotation curves of the FE model compared to test the results	72

8.1	Investigated welded beam-to-column connection	74
8.2	Finite element local model for Example 1 to perform virtual tests	75
8.3	Modified slenderness ratio of column web plotted with buckling curves	77
8.4	Case 1 (a) Von Mises Stress (b) $M_x - \phi_x$ relationship	78
8.5	Case 2 (a) Von Mises Stress (b) $M_x - \phi_x$ relationship	79
8.6	Case 3 (a) Von Mises Stress (b) $M_\gamma - \gamma$ relationship	80
8.7	Case 4 (a) Von Mises Stress (b) $M_x - \phi_x$ relationship (c) $M_\gamma - \gamma$ relationship	81
8.8	Case 5 (a) Von Mises Stress (b) $M_x - \phi_x$ relationship (c) $M_\gamma - \gamma$ relationship	82
8.9	Case 6 (a) Von Mises Stress (b) $M_x - \phi_x$ relationship (c) $M_\gamma - \gamma$ relationship	83
8.10	Case 7 (a) Von Mises Stress (b) $M_x - \phi_x$ relationship (c) $M_\gamma - \gamma$ relationship	84
8.11	Case 8 (a) Von Mises Stress (b) $M_x - \phi_x$ relationship (c) $M_\gamma - \gamma$ relationship	85
8.12	Case 9 (a) Von Mises Stress (b) $M_x - \phi_x$ relationship (c) $M_\gamma - \gamma$ relationship	86
8.13	Case 10 (a) Von Mises Stress (b) $M_x - \phi_x$ relationship (c) $M_\gamma - \gamma$ relationship	87
8.14	Two-surface law derived from local numerical model	88
8.15	Composite frame with welded connections	89
8.16	Two-surface constitutive law for the macro elements that model the connec- tion regions	89
8.17	Element types in frame analysis	90
8.18	Deformed frame from analysis in SLang	90
8.19	Load paths of each corner	91
8.20	Strain of central corner 3 close to weld rupture	92

List of Tables

2.1	Basic joint components	27
6.1	Geometric input to generic model creating the two examples of Figure 6.3 .	47
8.1	Geometry Example 1	74
8.2	Types of material and material parameters	74

Chapter 1

Introduction to composite beam-to-column connections

In this chapter, the general idea of composite structures in construction is given briefly. The background of composite connections is emphasised because it is the main topic of this research. Finally, the research of composite connections during the last fifteen years is summarised.

1.1 General

A Composite structure is a structure that is combined of two or more materials. There are many possible materials to be connected as composite materials. But in civil work, the combination of steel and concrete is the most important and widely used as construction materials, applied for buildings illustrated in Figure 1.1 as well as bridges. Composite members as conventional composite beams, composite columns and composite slabs have been used already for several decades. Steel and concrete can be utilised not only in mixed structural systems, such as concrete cores encased by steel tubes, but also in composite structures where members composing of steel and concrete act together compositely. Although these two materials have different natures, they support one another: Concrete is efficient in compression and steel in tension. So where steel components must resist compression, concrete can restrain these against buckling. One more advantage is concrete also gives protection against corrosion and provides thermal insulation at high temperatures. Composite and mixed building systems of structural steel and reinforced concrete are increasingly designed to produce more efficient structures when they are compared to design using either steel or reinforced concrete alone. Mixed building systems mean using elements or members of different types in construction, such as bare steel, reinforced concrete, prefabricated elements. Moreover, using rolled steel sections, profiled metal decking and/or prefabricated composite members can reduce the construction period. It leads to reducing the construction costs. Additionally, the joints can be fabricated in a factory and erected on site for the most efficiency and economic way [Bode, 1998, Huber, 2000].

Figure 1.1: Composite construction in buildings [Lecture notes, Stahl- und Verbundbau, Universitaet Kassel]

1.2 Beam-to-column connection

A composite connection may be defined as a joint between members where one or more of the members is a composite section and the reinforcement connecting the members is intended to contribute to the resistance, stiffness and ductility of the joint. Beam-to-column composite joints comprise of steel beam, a continuous reinforced concrete slab and steel or composite column. With this definition the connections in a variety of different forms of construction can be considered and designed as composite connections, such as the beam-to-column connections in a steel frame where the columns are non-composite (bare steel, 'I', 'H', or box section) and the beams are designed to act compositely with the floor slab. In this type of structure the floor slab may consist of any of the following forms of floor construction:

- concrete acting compositely with a profiled metal decking
- an in-situ flat slab
- a flat slab constructed from pre-cast concrete units [Nethercot, 2003].

Figure 1.2 illustrates a typical composite connection, which consists of a steel joint and a concrete slab with reinforcement across the joint.

Figure 1.2: Typical composite connection [Nethercot, 2003]

1.3 Types of connections

Different types of bare steel connections can further increase the range of possible composite connections. For example, the following different types of bare steel connection can be used:

- end plate connection (Figure 1.3b and 1.3d)
- fin plate connection (Figure 1.3c)
- fully-welded connection
- flange and web clear connection (Figure 1.3a)
- contact plate.

Some of these details used as part of a composite connection are shown in Figure 1.3 [Nethercot, 2003].

[Bode, 1996] and [Nethercot, 2003] expressed six types of moment resisting composite beam-to-column joints which are commonly used in frames as shown in Figure 1.4:

- Joint with welded connection
- Joint with end plate connection
- Joint with partial depth end plate connection
- Joint with fin and connect plates
- Joint with cleated connections
- Joint with contact plate

Figure 1.3: Practical types of connections: (a) Cleated connections; (b) full depth end plate; (c) fin plate connections; (d) partial depth end plate [Nethercot, 2003]

Figure 1.4: Types of beam-to-column connection: (a) Welded connection; (b) full depth end plate connection; (c) partial depth end plate connection; (d) fin plate connection with connect plate; (e) cleated connection; (f) contact plate [Nethercot, 2003]

Figure 1.5: Characteristic joint properties [Bode and Kronenberger, 1997]

Welded connections have high stiffness and strength but on-site fabrication and installation costs are quite high. Moreover the welded connections require small tolerances. Continuous beam behaviour can be assumed as long as local instabilities do not occur. End plates, fin plates or cleated connections as well as connections without bolts also can be utilised. The last type with contact plates can be assumed to be hinged during erection but after the concrete has hardened it provides a higher stiffness and moment resistance. The structural system changes from simply supported during erection to semi-continuous after hardening of the concrete. Beams and columns of these beam-to-column joints can be encased with concrete. This additional concrete part increases the fire resistance as well as resistance and stiffness of joint components [Bode, 1996].

1.4 Behaviour of composite connections

The following properties (see Figure 1.5) generally define connection behaviour:

- Initial stiffness S_{ini}
- Moment resistance $M_{R,j}$
- Rotation capacity ϕ_u

Stiffness, resistance and rotation capacity depend on the load-deformation relationships of the single joint components and the behaviour of composite joints differs from the behaviour of the bare steel connection. The actual moment-rotation curve of a composite connection is normally nonlinear. [Bode, 1996] concluded that the behaviour of composite joints is mainly influenced by the type, amount and distribution of reinforcement and shear

Figure 1.6: Non-linear moment-rotation behaviour of a joint and classification of composite connection EC3 and EC4

connectors. Also the type of loading (balanced or unbalanced), the joint configuration (single or double sided joints), the loading history (propped or un-propped during concreting) and possible changes in the structural system influence the joint behaviour.

1.5 Classification of composite connections

[Bode, 1996] and [Huber, 2000] stated that connections can be classified by two criteria:

- stiffness:

A joint with vanishing rotational stiffness and which therefore carries no bending moment is called a pinned joint. A rigid joint is one whose rigidity under flexure is more or less infinite and which thus ensures a perfect continuity of rotations. In between these two extreme boundaries they are semi-rigid joints.

- strength:

In contrast to a pinned joint a joint whose ultimate strength is greater than the ultimate resistance of the parts whose linkage it ensures is called a full strength joint. Again a partial strength joint represents a middle course between these extremes. In Eurocode the terms ‘strength’ and ‘resistance’ are used with an identical meaning.

Figure 1.6 shows the non-linear moment-rotation behaviour of a joint in principle, together with the classification regarding stiffness and strength.

Although the classification of connections was stated in Eurocode 3 for bare steel connections, it can be applied to composite connections. The real behaviour of beam-to-column connection of composite frames is very important in analysis and design work. Traditionally the joints have simply been regarded as a part of the column and not been considered in the global calculation. Traditionally joints were considered as pinned or rigid. But in reality both assumptions are quite conservative and are uneconomic. The influence of the joints on the global behaviour is such that, the old-fashioned philosophy of perfect hinges or rigid full-strength restraints may lead to the wrong interpretation of the structural behaviour in terms of load-resistance and deformations. Thus, to achieve economy and safety the real behaviour of composite connections as semi-rigid connections must be taken into consideration in the analysis and design. In order to allow for semi-rigid connection effects to be included in frame design, a knowledge of three characteristics; the moment capacity, rotation capacity and rotational stiffness of the connections, is required. Of these three quantities the moment capacity is the most important because the other two properties may be ignored in plastic design when sufficient rotation capacity of the connections is guaranteed by adopting suitable details [Bode, 1996, Huber, 2000, Li et al., 1996b].

1.6 Failure modes observed in connection tests

Identification of all possible failure modes for the connections is the basis for determining connection moment capacity. Any premature failure of an individual component should be recognised and prevented. Failure of a composite connection can be either non-ductile (bolt failure, reinforcement fracture, slab failure in shear etc.) or ductile (excessive deformation of connection components). According to one hundred and fifty tests conducted worldwide, fifteen possible failure modes have been identified for composite end plate, fin plate and web cleat connections as illustrated in Figure 1.7 [Li et al., 1996b, Nethercot et al., 1996].

- Yield of column flange in bending
- Yield of local buckling of column web in transverse compression
- Yield or local buckling of column web panel in shear
- Yield or buckling of beam lower flange in compression
- Yield or buckling of beam web in compression and shear
- Yield or fracture of slab reinforcement in tension
- Anchorage failure of reinforcement for external column connections
- Yield or fracture of bolts in tension
- Failure of slab in shear

- Crushing failure of concrete slab against column face on the lower moment side of the connection (extremely non-symmetrically loaded connections)
- Shear connector failure or concrete failure around the shear connectors
- Fin plate twisting
- Yield of end plate in bending
- Weld failure between steel beam and end plate
- Excessive connection deformation

Figure 1.8 to Figure 1.11 from [Nethercot, 2003] present some modes of failure occurring in composite connection.

1.7 Literature survey

In this section, a brief review of previous studies on composite connection in the last fifteen years is presented. Over the past 40 years numerous research in this field has been done in many countries all over the world, especially in Europe. The semi-rigid and partial strength behaviour of composite joints has stimulated researchers' curiosities for a few decades. During the last two decades, there has been extensive research on composite joints as semi-rigid connections and also many efforts to predict the joint behaviour. As a result, they led to the new approach, so-called component method. Firstly, this method was developed for steel connections. Afterwards, it was also applied to composite connections. The component method for composite connections will be explained and discussed in Chapter 2.

There have been two main approaches for investigating composite connections, i.e. experimental approach and numerical approach. Previously, mostly laboratory testing was done to examine the real connection behaviour. Using a numerical approach, particularly finite elements in order to investigate the behaviour of composite connections is quite a complicated task due to the large number of variables and potential failure modes associated with composite connections. Both approaches support each other to obtain better understanding and prediction of composite connection behaviour. It is quite clear that nowadays the tendency of new studies on composite joints is cyclic loading instead of monotonic loading. Consequently, the European Union has promoted research efforts in order to improve the knowledge in the domain of earthquake resistance of steel-concrete composite moment resisting frame structures and their components.

1.7.1 Research in Germany

In 1991 a research group supported by the DFG (German Research Foundation) was established at University of Kaiserslautern to investigate the behaviour of composite structures.

(a) Composite flush endplate connection

(b) Composite angle cleated connection

(c) Composite finplate connection

Figure 1.7: Observed failure modes for composite connections [Nethercot et al., 1996]

Figure 1.8: Typical weld failure in a composite end plate connection [Nethercot, 2003]

Figure 1.9: Complete end plate yielding [Nethercot, 2003]

Figure 1.10: Combined bolt fracture and yielding of the end plate [Nethercot, 2003]

Figure 1.11: Buckling of the beams compression flange and web [Nethercot, 2003]

Consequently, research on composite connections in Germany was conducted under this project.

[Bode, 1996] described the types of joints and the moment-rotation behaviour of composite joints in order to highlight their influence on the behaviour of semi-continuous beams, particularly on composite beams with partial strength connections. He conducted twenty-one symmetrically loaded cruciform tests of composite joints. In these tests beam-to-beam as well as beam-to-column joints were investigated. Extended and flush end plate connections were used as well as fin plate and boltless connections (connections with contact plates). Besides the experimental investigations the composite beam-to-column joints were modelled by simple springs. The comparison of load-rotation curves between the measurement and the calculation from spring model was presented.

[Ramm and Elz, 1996] investigated the influence of reinforcement on the development of cracks and the behaviour of composite slabs as part of composite beams in negative bending moment areas. The experimental investigations and parameter studies by calculations were carried out at the University of Kaiserslautern. They found that the development of cracking in slabs as part of composite beams was decisively influenced by the transverse reinforcement and cracking of the slab arose very early in the connection area. And tensile tests on reinforced concrete showed that the ductility essentially depended upon the percentage of reinforcement and the stress-strain behaviour of the reinforced bars.

In order to determine the rotation capacity of typical partial strength composite connections in buildings, sixteen tests with three different types of connection, namely beam-to-column connection, beam-to-beam connection and beam-to-column connection with transverse compression, were carried out by [Kathage and Kindmann, 1996]. They concluded that the plastic hinge theory could be applied to continuous composite beams with typical composite connections, especially partial strength connections. And it leads to an economic design of the connections as well as of the structure itself.

[Bode and Odenbreit, 2000] presented a method to define the rotational spring-stiffness and the bending resistance of several types of composite connections with the help of test results and the observed rotational and load-bearing behaviour of composite connections. The method was applied to a large-scale test series, which was already conducted at Kaiserslautern University [Bode et al., 1999]. The introduced model gave an easy method to analyse the load bearing capacity and the deformations of composite beams with the special consideration of the composite connections. A proposal for the design of composite beams with a special consideration of the composite connection was given as illustrated in Figure 1.12. In comparison with the nonlinear analysis, the results were on the safe side and are a good compromise between safety on one hand and economy on the other.

1.7.2 Research in the United Kingdom

In the 1990's, Nethercot and his group at University of Nottingham have concentrated on composite connections between steel columns and composite beams with simple end plate steel connections because they are commonly used in the United Kingdom.

In an attempt to understand and explain the characteristics of composite beam to

Figure 1.12: Model of a composite beam with composite connection
[Bode and Odenbreit, 2000]

column connections, a large number of composite joints have been tested during the past three decades. A series of tests designed to investigate the interaction of a variety of different steel beam to column details with a composite metal deck floor was also carried out by [Xiao et al., 1994]. The main emphasis was on assessing the three key indications of performance: moment resistance, rotational stiffness and rotation capacity that could be used in frame design to represent the realistic semi-rigid and partial strength behaviour. Specimens were selected to include several currently used joint types, i.e. seating cleat with double web cleats, flush end plates, partial depth end plates and fin plate as shown in Figure 1.13, as well as to investigate slab parameters expected to influence the connection behaviour directly.

Previously, most of the tests were conducted on cruciform specimens with symmetrical loading and a constant and relatively low shear/moment ratio. Moreover, almost all tests only gave the connection moment-rotation curves and a visual indication of the failure modes. These are not always adequate for a full understanding of the connection behaviour and are insufficient for the detailed calibration of numerical models. In order to investigate the effects of shear and non-symmetrical moments on composite connections, [Li et al., 1996a] conducted a test series of seven end plate beam-to-column connection. These included one pure steel connection and six composite connections. The main variables investigated were the degrees of unbalanced moment and the shear/moment ratio. Comprehensive instrumentation has been used to monitor: beam strains, column strains, rebar strains and bolt forces as well as member and connection deformations. This comprehensive monitoring leads to a full understanding of the behaviour of this kind of connection. In addition, the large number of recorded variables provides data for the detailed validation of numerical analyses.

Although many methods have been proposed for predicting composite connection moment capacity, these concentrated on symmetrically loaded connections and neglected the shear force effect. But in practice, connections are not always in a situation of symmetri-

Figure 1.13: Four types of steel joints [Xiao et al., 1994]

cal load and low shear forces, therefore [Li et al., 1996b] also developed a comprehensive method based on their experimental data and the EC3 method for bare steel connections for predicting the moment capacities of flush end plate composite connections including the effects of both non-symmetrical moments and shear/moment ratios.

[Nethercot et al., 1996] proposed a unified design method covering the prediction of both moment capacity and rotation capacity for composite flush end plate connections by starting from insights into connection behaviour gained from physical testing and numerical simulation. The basis of this design method is the component method of EC3 and the stress block concept. Thirty-two laboratory tests from seven different sources were used to verify the proposed model that could consider the effect of the shear to moment ratio and axial column loading.

As stated, knowledge of the initial rotational stiffness of a connection is very important for the global elastic analysis of frame structures, because design on the basis of partial strength and/or semi-rigid joint action has been formally recognised in Eurocode 3 and Eurocode 4. [Ahmed and Nethercot, 1997] used the proposed design model as the basis for the development of parallel methods to predict initial stiffness and rotation capacity of composite flush end plate connections. They validated the predictions for both properties against all available test data and the predictions demonstrated both the accuracy and consistency of the method.

The behaviour of five semi-rigid composite end plate connections with precast hollow core slabs was examined by [Lam and Fu, 2004] at University of Leeds. Experiments were

carried out to investigate the joint rotation characteristics and ultimate moment capacity of the composite beam-to-column connections. In this study different level of shear connection, spacing and position of first studs from the column face were tested. From the results, adequate shear connection should be provided to enable full mobilisation of the longitudinal reinforcement and partial shear connection will lead to low moment and rotation capacity as the longitudinal bars cannot be fully mobilised. Close spacing of the shear stud near the column face affects the crack pattern and demands a high degree of elongation of reinforcement to achieve the same rotation capacity of the same joint with large spacing to the first stud position. Moreover, it was recommended that the first stud should be placed at a spacing equivalent to two times the column width.

1.7.3 Research in other countries

[Crisinel and Carretero, 1996] proposed a practical and simple method for the prediction of bilinear moment rotation characteristics of web cleat beam-to-column connections, i.e. moment resistance and rotational stiffness, by taking into account the continuous reinforced concrete slab. This method was based on an existing method for end plate connections. Comparisons with test results and numerical simulations using a nonlinear finite element analysis showed that the predicted behaviour was satisfactory. They found that bilinear characteristics determined by simple hand calculations could be easily used in the design of semi-continuous composite structures.

An analytical procedure to simulate the nonlinear moment-rotation characteristics of semi-rigid composite beam-to-column connections with flush end plates was proposed by [Shi et al., 1996]. They verified the proposed analytical model against the available experimental results and concluded that this analytical model could give sufficiently accurate predictions of yielding moment and the tangent stiffness. An exponential equation was recommended to represent connection behaviour, so that it can be directly incorporated into the non-sway composite frame analysis taking into account the behaviour of complicated semi-rigid connections. The maximum moment resistances were consistently underestimated by this model. To improve the proposed model they included the effect of strain hardening and post yielding strength in further research.

[Huber and Tschemmerneegg, 1997] investigated the real behaviour of beam-to-column composite connections based on the component model method. The frame analysis in consideration with this method was presented. The objective of this study is to present the practical advantage of this new analysis philosophy, i.e. semi-rigid connections, and its application

[Aribert et al., 1997] presented the criteria to classify composite joints by strength, i.e. full strength, partial strength and nominally pinned and illustrated the application of these criteria to some composite joints tested in the laboratory. A simplified analytical procedure was also summarised in order to evaluate the moment-rotation curve and the rotation capacity of composite joints with a good approximation. Finally, they advised that design based on rigid-plastic global analysis should be used when composite joints in a brace frame are partial strength.

A design method for braced frames comprising semi-continuous partial-strength composite joints was proposed by [Crisinel and Kattner, 2000]. In this design method, the ultimate load carrying capacity was calculated by considering the plastic moment resistance of the composite joint in the hogging moment region as well as a defined percentage of the plastic moment resistance of the composite beam in the sagging moment region. The defined percentage depended on the required rotation at the support and was based on the assumption of a certain available rotation of the composite joint. This assumption was assured by design recommendations for composite joints on the basis of existing experimental studies.

A numerical model for flush end plate composite beam-to-column connection was proposed by [Aribert and Dinga, 2000]. This model (see Figure 1.14) was based on the component method by using simplified spring models to represent the specialised components, i.e. the shear connector, the concrete slab reinforcement including possible tension stiffening effect and the flexural bending of the bolted flush end plate (especially for the part between the upper bolt-row and the tension flange of the steel beam). The model was compared with several test results with cruciform joint configuration under symmetrical loading which were carried out at the National Institute of Applied Sciences (INSA) of Rennes in France. The established numerical model was in rather good agreement with the tests and could suitably predict the key properties of the composite joints: initial rotational stiffness, moment resistance and rotation capacity.

The cyclic, nonlinear analysis of frames composed of steel columns, steel-concrete composite girders and partially-restrained composite (PRC) connections were studied by [Alemdar et al., 2000]. The effect of the slab around the column was modelled by partial composite beam finite elements, component-based connection models and slab load transfer elements. The key characteristics of this approach were outlined via an example analysis of a two-bay experimental test. It was concluded that the presented analysis approaches could provide a reasonable representation of the complex load transfer mechanisms within PRC joints.

[Clemente et al., 2004] adopted the component modelling approach for the analysis and simulation of composite connections in structures. One of the advantages in adopting the component modelling approach is that it is possible to closely simulate the local behaviour of a number of connecting members, and to put it directly in a relationship with the overall simulated behaviour, thus highlighting patterns and providing explanations, which might not have been immediately discernible just by examining experimental data only. An experimental test involving – two one-storey, two-bay steel-concrete composite frames with partially-restrained connections, subjected to a series of loading and unloading cycles up to failure was discussed and the simulation of two experimentally tested steel-concrete composite sub-frames with partially-restrained connections was described. The experimental data was interpreted by means of a mechanical model of the connections. The analysis of the structural behaviour by means of the proposed modelling approach allows to closely relate the experimentally observed phenomena to the local behaviour of single components, such as the connecting elements, the steel-concrete interface, the column web panel, etc., with good accuracy. Comparisons between the numerical and the experimental

Figure 1.14: Different components of the composite joint model [Aribert and Dinga, 2000]

data were presented and discussed. Especially, some numerical-only results were shown and discussed, allowing for some previously impossible in-depth look at the internal forces redistribution, reaction force history, neutral axis shift, etc. [Clemente et al., 2004] concluded that the mechanical model employed for the simulations proved to be an invaluable tool for the interpretation of experimental data; the flexibility of definition of the model characteristics renders it also potentially usable for virtual experiments, to complement and expand the scope of laboratory tests.

Numerical and analytical investigations performed on composite sway frames under static loading at Liege University, as part of a European project, were presented by [Maquoi et al., 2004]. The objective was to study the in-plane behaviour of composite sway frames. In this paper, the validity of the homemade FEM software FINELG for the numerical simulation until failure of composite structures was shown. A detailed numerical study of a composite sway frame tested in Bochum, Germany was achieved as an example. Finally, the applicability of simplified analytical methods used for steel sway frames was investigated.

Monotonic and cyclic tests were conducted by [Salvatore et al., 2004] at the University of Pisa. They expressed that exploitation of dissipative partial strength beam-to-column joints could guarantee the formation of global frame mechanisms and the dissipation of high amounts of hysteretic energy. The inelastic response of joints was divided mainly between shear yielding of the column web panel and inelastic bending of the extended end plate and column flange. Yielding of the reinforcement and concrete crushing of the slab against the column flange also occurred. In order to guarantee a ductile behaviour of partial strength beam-to-column composite joints, a suitable capacity design of joints mechanical components is required. However, mechanical models of composite joints under seismic actions were not fully defined yet and many doubts still exist mainly with strut and tie mechanisms in the reinforced concrete slab governing the force transfer between beam and column. In this research, mechanical models of interior and exterior beam-to-column joints illustrated in Figure 1.15 were presented on the basis of experimental results obtained in monotonic tests through the analysis and modelling of each component part governing their structural behaviour. A preliminary validation of the models was presented and discussed.

[Lachal et al., 2004] also performed three monotonic and nine cyclic tests of end plate beam-to-column composite joints at the National Institute of Applied Sciences (INSA) of Rennes in France. Both exterior and interior joints of frames were considered with two types of loading; symmetrical and unsymmetrical loading. The dissipation of plastic energy was made either inside the joint using thin end plates or outside the joint in the connected beam using bolted end plates strengthened by adjacent haunches. The cyclic testing procedure recommended by the European Convention for Constructional Steelwork (ECCS) was applied in order to simulate severe seismic actions. The experimental results were discussed in terms of rotational stiffness, moment resistance, rotational ductility and low-cycle fatigue with comparisons to analytical models given in Eurocode 3 and 4. This analytical model is based on the component method. As the results, [Lachal et al., 2004] accepted that Eurocode 3 and 4 offer static design methods which are able to predict

(a) Mechanical model of the interior joint

(b) Mechanical model of the exterior joint

Figure 1.15: Mechanical models of joints [Salvatore et al., 2004]

the moment resistance and the initial stiffness of a steel or composite end plate bolted connection with a good accuracy. Nevertheless, in cyclic loading, the initial stiffness was generally smaller than the predicted one whereas the moment resistance appeared to be predicted suitably. And it is necessary to assure the ductility and resistance performances of every component of the joint in order to obtain an optimal seismic design of a composite connection.

The seismic performance of a realistic size moment resisting frame structure of high ductility under various levels of earthquakes was investigated by [Bursi et al., 2004]. Dissipative elements were conceived to be partial strength beam-to-column joints and column base joints at later stage. Pseudo-dynamic and cyclic test results confirmed that properly designed and constructed partial strength beam-to-column joints and partially encased columns without concrete in column web panels exhibited a favourable behaviour in terms of energy dissipation, limited strength degradation and ductility. In order to complement the experimental program, a series of inelastic dynamic analyses were also performed on a two-dimension moment resisting frame to study the influence of joint deformation and design philosophy on the overall behaviour of steel-concrete composite systems. [Bursi et al., 2004] concluded that simulation and implementation in FE codes of the deteriorating behaviour of dissipative components of beam-to-column and column base joints by means of robust hysteretic models deserve additional studies.

Chapter 2

Component model method

In the past, composite connections were analysed and designed as rigid connections or as ideal pinned connections. Both of these 2 ideal assumptions are uneconomical and can lead to doubtful frame analysis in consideration of safety and serviceability, since the connection behaviour significantly affects to moment-rotation characteristics of the whole structure. Consequently, there have been numerous studies on composite joints as semi-rigid connections and also many efforts to predict the joint behaviour during the last three decades. The Component model method was proposed in 1980s to describe the semi-rigid behaviour of the composite connections and is referred in Eurocode 4.

The concept behind the component model has been mainly developed and studied in Europe by [Huber and Tschemmernegg, 1997] and [Huber, 2000].

A description of the rotational behaviour of a joint has to take into account all sources of deformations within the joint area. Moreover, all possibilities of local plastic deformations and instabilities have to be covered by such an analytical model. The large number of influencing parameters was the reason, why the first attempt to develop a component method directly based on full scale joint tests has been judged as a failure. A second research with the aim of finite element modelling was not really fulfilled because of local detailing problems. Therefore, for the analytical determination of the nonlinear joint response, a macroscopic inspection by subdividing the complex joint into so-called simple ‘*components*’ proved to be successful. In contrary to the classical finite element method which deals with stress and strain, the components are logical subsystems of the joint exposed to inner forces and deformations. As it will be described later in detail, these components can be understood as translational springs with nonlinear force-deformation behaviour. All considered components can be tested in clear, relatively cheap so-called ‘*component tests*’, on the basis of which theoretical models can be developed. Finally, the total joint response (reproduced in the joint model for global analysis) could be derived by assembling all influencing components in the correct manner based on the so-called ‘*component method*’. The Component method was first proposed at the beginning of 1980’s in Innsbruck.

Several testing series for steel joints have successfully been worked out at many research centres in Europe. As a result, a high standard of knowledge on the connection technique

Figure 2.1: Forming of groups at the end plate connection for the Innsbruck component model

for bare steel frames is available. Based on the gained experience a model to describe the behaviour of beam-to-column joints in composite and mixed construction was investigated by means of the component method. All steel components could directly be taken from the steel model. Only the additional concrete components had to be analysed. Nowadays, the component method is accepted all over Europe and has already been used very successfully for developing simplified design rules for Eurocode 3 and Eurocode 4. This method offers the advantage of a minimum of testing costs, clear physical calculation models for the components and a maximum flexibility for the designer, who is able to combine a multitude of available components to a most economic joint configuration.

The component model for steel connections and later that for composite connections has been developed by dividing the complex joint into logical parts exposed to inner forces and therefore being the sources of deformations. The connecting and panel zone are distinguished in horizontal direction. In vertical direction the tension, the compression and the shear regions are classified. Figure 2.1 shows the six action groups forming in end plate composite connections. The corresponding component models for steel and composite, both developed in Innsbruck, can be seen in Figure 2.2. Till now, no interaction between several components themselves is taken into consideration. So, there are only diagonal elements in the joints stiffness matrix, the other elements are neglected.

Each translational spring (representing a component group) can again be subdivided into basic components, the smallest parts within a joint. Such as the composite shear spring, which consists of the components steel web panel in shear, steel web panel in bending and concrete encasement in shear. Analogously, the composite compression spring can be divided into a steel part and a concrete part in compression and so on. It can be summarised that wherever the displacements occur within component groups, the basic components are acting in series. And where components are sharing inner forces and therefore are increasing stiffness and resistance they are acting in parallel. The refined

Figure 2.2: Innsbruck component model for steel and composite connections [Huber and Tschammerneegg, 1997]

composite component model following these considerations is shown in Figure 2.3. All sixteen basic joint components and the corresponding zones and regions are given in Table 2.1. The new additional components when extending the component model from steel to composite are the concrete encasement in compression (No. 2, 4), the concrete slab in tension (No. 11, 12, 13) and the concrete encasement in shear (No. 16).

For the purpose of simplicity in Eurocode 3, a different component model to that developed in Innsbruck has been used. As Eurocode 4 should be based on Eurocode 3, this simplifying philosophy has been adopted. As illustrated in Figure 2.4 the two component models are different in the following two points. Firstly, the missing separation between panel and connecting zone in the Eurocode model may lead to a non-straight deformation of the column front in contradiction to test experiences. And further the interplay between tension and compression components within the web panel, which exists in reality, is prevented by a stiff separation bar in the Eurocode component model.

Even though the component model developed to be incorporated in the analysis and as a background of international codes like Eurocode 4 are very advantageous, they are rather unwieldy in applications with a multitude of parameters to be specified and changed during the design process. In addition, these models may not be able to capture important local failure states with good accuracy (like weld ruptures or plastic plate buckling) or neglect complete deformation and stress states like the vertical action due to the forces and moments in the columns [Dorka and Amorntipsakul, 2008].

Figure 2.3: Refined component model [Huber and Tschemmerneegg, 1997]

Figure 2.4: Comparison of Innsbruck component model and Eurocode component model [Huber and Tschemmerneegg, 1997]

No.	Components	Zone	Region
1	Interior steel web panel	Panel	Compression
2	Concrete encasement	Panel	Compression
3	Exterior steel web panel (Column flange and local effects)	Panel	Compression
4	Effect of concrete encasement on exterior spring	Panel	Compression
5	Beam flange (Local effect), contact plate, end plate	Connecting	Compression
6	Steel web panel including part of flange, fillet radius	Panel	Tension
7	Stiffener in tension	Panel	Tension
8	Column flange in bending (Stiffened)	Connecting	Tension
9	End plate in bending, beam web in tension	Connecting	Tension
10	Bolts in tension	Connecting	Tension
11	Reinforcement (Within panel) in tension	Panel	Tension
12	Slip of composite beam (Due to incomplete interaction)	Connecting	Tension
13	Redirection of unbalanced force	Panel	Tension
14	Steel web panel in shear	Panel	Shear
15	Steel web panel in bending	Panel	Shear
16	Concrete encasement in shear	Panel	Shear

Table 2.1: Basic joint components [Huber, 2000]

Chapter 3

State of the art FE models

3.1 Finite element model developed by Ahmed et al.

To simulate the response of semi-rigid composite end plate connections, [Ahmed et al., 1995] proposed finite element models for composite connections by using ABAQUS, a nonlinear general purpose software. The objective of their study was to develop a finite element model that faithfully represents all aspects of the physical behaviour of composite end plate connections that were observed in physical tests. Validation of the modelling was assisted by the availability of a comprehensive database of all known composite connection test results, especially the very detailed test histories that were produced in the series conducted in the University of Nottingham. They stated that the developed model could address the important joint characteristics of variation of reinforcement area, position of application of load, degree of shear interaction, changes in material properties, interface separation and closure, slip between slab (reinforcement) and beam top flange and bolts in realistic fashion.

[Nethercot and Ahmed, 1996] continued developing the finite element model. They described the modelling of the cruciform connections with symmetrically applied loading in their paper. In addition to the modelling of composite beam-to-column end plate connections, the modelling of a composite non-sway frame, verified against the results of full scale tests, was also presented. Their studies also provided particular insights into key aspects of the behaviour of connections, such as the effect of the shear to moment ratio and the influence of coincident column loading, which would not have been possible using the experimental approach alone. The general conclusion drawn from all of these studies was that, since FE modelling could accurately represent all the main features of the behaviour of composite end plate connections, it offers a reliable and very cost-effective alternative to laboratory testing as a way of generating results.

Formerly, all studies of composite connection behaviour and of the performance of composite frames virtually relied upon laboratory testing. The number of variables involved in a composite connection is large, with the behaviour of the connection being affected by steel beam, column, reinforcement ration, type of loading and connection symmetry or

Figure 3.1: Finite element model from [Ahmed et al., 1995]

non-symmetry, number of bolt rows, type and number of shear studs, and the presence of metal decking, besides the details of the connection arrangement and the material properties. Thus fourteen different failure modes have been observed in the tests conducted world wide and presented by [Nethercot et al., 1996]. Due to this complexity, it would be expensive and time consuming to attempt to study the problem solely on the basis of testing. Additionally, [Nethercot and Ahmed, 1996] stated that it is also not possible to record the load-strain history and other detailed aspects of behaviour for all components over their full area, immaterial of the resources used. Finite elements possibly could be used to study connection response at any required point, as well as to consider its overall features provided the model is correctly developed.

In their study, shell elements were used with nonlinear material law for the steel parts, gap elements between the end plates and column flanges and beam elements to model the shear studs. They used simplified elements of spring-type to model the behaviour of the bolts and their surrounding and the reinforcement action in the cracked concrete. It was observed during the numerical modelling, once the slab starts cracking, the increment in load becomes very small and the solutions virtually stop at that point, therefore the concrete part of the connection was neglected for connections with downward loading in their study and was represented through the combination of multipoint constraints in the beam and the modelling approach of the shear studs. Figure 3.1 shows the finite element mesh used in their analyses. They obtained good results compared to tests.

As already stated, [Nethercot and Ahmed, 1996] proposed this finite element model in order to represent all aspects of the physical behaviour of composite end plate connections that were observed in their physical tests. And to avoid convergence problems due to cracking of slab, they neglected the concrete part of the connection under hogging moment that plays an important role under sagging moment. Only half of the composite beam- to-column connections were modelled due to symmetry of loading. It means that this model cannot represent the shear state. For these reasons this finite element could not be utilised

in general aspects. Moreover, such local models require thousands of degrees of freedom so they also cannot be used directly in practical frame analysis.

3.2 Finite element model developed by Leon et al.

A combined experimental and computational research program was undertaken at the University of Minnesota to study the influence of floor slabs on the strength, stiffness and fracture performance of steel moment-resisting frames. The computational work included both macro-level and micro-level finite element analysis. The macro analyses emphasised the effects of the earthquake at a building system level, while the micro analyses and experimental research focused on the behaviour of the joint. These macro analyses were compared with a detailed description of the damage to structures during the Northridge, California earthquake of 17 January, 1994. The analyses clearly showed these structures, whose design was predominantly controlled by stiffness, were subjected to force and deformation levels substantially higher than those generated from an equivalent static analysis similar to that used for the design. [Leon et al., 1996] described the results of tests on three full-scale specimen of a typical interior moment-resisting beam-to-column connection, one a bare steel specimen and two with a composite floor slab, along with corroborating macro and micro analysis results in order to investigate the brittle fracture failure of numerous welded steel moment-resisting connections during the Northridge earthquake. A series of three-dimensional, static, monotonic continuum analyses by using finite elements were also conducted to corroborate the experimental results. These results, which showed evidence of both brittle and low cycle fatigue fractures, helped to explain the predominance of bottom flange failures, and they indicated that changes may be required in design codes, which ignore the effects of unintended composite floor action.

Brick elements were used to model steel and concrete parts. Fracture, bolts and bolt slip were not modelled, nor were the metal deck or shear connections; the concrete slab was assumed to be bonded integrally to the steel beam. Figure 3.2 shows longitudinal strains through the finite element model of the composite girder in positive bending. In order to avoid convergence problems resulting from a sharply softening tensile stress-strain curve for tension in the slab, elastic-perfectly plastic behaviour, rather than strain softening was assumed in their model.

[Leon et al., 1996] showed that their finite element model could represent end plate composite beam-to-column connections under both positive bending moment and negative bending moment. They concluded that the strengths achieved correspond well with the experimental connections which failed by low cycle fatigue and the strength in positive bending of the composite analysis is close to that of a fully composite strength calculation (assuming the plastic neutral axis in the slab) But they did not show the stiffness obtained from their finite element model comparing to the stiffness obtained from experimental results. Thus, the finite element model developed in this study is not convenient to be used for other purposes.

Figure 3.2: Finite element model from [Leon et al., 1996]

Chapter 4

Macro element approach for scaling

As discussed in Chapter 2, although the component model method is very useful, it also has some shortcomings especially when it is used in practical frame analysis. Therefore, the macro element approach for scaling as the basic background of this dissertation is explained in this chapter.

4.1 Macro elements for scaling

The Macro elements considered in this work were first introduced as discrete elements by [Dorka, 1991]. He gave a brief review of governing equations for discrete systems and the virtues of the approach was illustrated with two examples: A triangular elastic element with a circular hole and a rectangular element which models the cyclic response of a building's shear wall containing a friction connection. [Dorka, 1991] concluded that by formulating the mechanics appropriately for each level of abstraction and utilising the principles of the theory of discrete mechanics, complicated structural systems can be analysed in an economical way without sacrificing their complexity. And the linear and nonlinear examples presented indicate the large potential of this approach in analysis, simulation and design of structural systems.

Recently, [Dorka and Amorntipsakul, 2008] have used this concept to model composite beam-to-column connections. Because there are severe shortcomings of the component model as discussed in the previous chapter, sophisticated local finite element models must be utilised to incorporate such effects. But nowadays the local finite element models are still not able to be incorporated in a regular practical frame analysis in any reasonable fashion. In order to solve these problems, the macro element approach for modelling beam-to-column connection regions was applied.

Firstly, the term of '*macro elements*' should be defined clearly to avoid being confused with the term normally used in finite element analysis. Macro elements, as stated in this study, are discrete domains with their mechanical behaviour described by a set of independent orthogonal boundary states, each consisting of displacements and forces associated by a one-dimensional constitutive relationship. Figure 4.1 illustrates examples for a plane tri-

Figure 4.1: Macro stresses and strains of a plane triangle, tetrahedron and plane quadrilateral [Dorka, 1991]

angle, tetrahedron and plane quadrilateral in which these states are only defined by nodal states and no assumption is required for the distribution over the boundaries or inside the domains.

An orthogonal state consists of a unique and independent boundary displacement and force pattern each determined by one variable termed ‘*macro stress*’ and ‘*macro strain*’. From these, the basic equations which govern a discrete system can be written:

$$\varepsilon_k = B_k u_k \quad \text{macro strain–nodal displacement relation} \quad (4.1)$$

$$\sigma_k = D_k \varepsilon_k \quad \text{macro constitutive relation} \quad (4.2)$$

$$f_k = B_k^T \sigma_k \quad \text{nodal force–macro stress relation} \quad (4.3)$$

$$K_k = B_k^T D_k B_k \quad \text{macro element stiffness matrix} \quad (4.4)$$

for the k^{th} element [Dorka, 1991].

The matrix B_k contains the transformations from nodal displacements to macro strains and is a geometric property of the element. D_k contains an element constitutive law which depends on the size and internal mechanics of the element and must be described for each instant. Because of orthogonality, a macro stress does work only on its associated macro strain. Thus, each macro stress is associated to its macro strain by a one-dimensional constitutive relationship which may be nonlinear. A Beam-type macro element with its constitutive relationships is illustrated in Figure 4.2. Combinations of these orthogonal states lead to combined constitutive relationships which are best described by surface models in the macro stress space (interaction surfaces in force space) together with appropriate flow rules, similar to the approach found in multi-dimensional material laws.

The domain of such a macro-element must be filled with a local model or its constitutive relationships may be determined through tests applying the orthogonal states alone and in combination. In modelling, there is no restriction regarding its level of detailing and no internal continuity is required. As an example, [Dorka, 1991] used a detailed finite element model and the exact solution for the stress distribution around a circular hole to present the solution for a plane triangular macro element with a circular hole at its centre.

Figure 4.2: Orthogonal boundary states for a beam-type macro element with associated one-dimensional constitutive relationships [Dorka and Amorntipsakul, 2008]

Here, the anti-metric moment and associated shear forces form the shear state and the symmetric moment forms the bending state. When it comes to nonlinear cyclic loading, a model with yield and failure surface (two-surface model) may be useful in combination with a kinematic hardening law. The stiffness matrix of a beam element as macro element excluding the normal state is given below [Dorka, 1988]:

$$K \cdot u = k_s \cdot \begin{bmatrix} 1 & \frac{l}{2} & -1 & \frac{l}{2} \\ \frac{l}{2} & \left(\frac{l^2}{4} + \frac{k_b}{k_s}\right) & -\frac{l}{2} & \left(\frac{l^2}{4} - \frac{k_b}{k_s}\right) \\ -1 & -\frac{l}{2} & 1 & -\frac{l}{2} \\ \frac{l}{2} & \left(\frac{l^2}{4} - \frac{k_b}{k_s}\right) & -\frac{l}{2} & \left(\frac{l^2}{4} + \frac{k_b}{k_s}\right) \end{bmatrix} \cdot \begin{bmatrix} v_i \\ \phi_i \\ v_{i+1} \\ \phi_{i+1} \end{bmatrix} \quad (4.5)$$

where l length of element
 k_b bending stiffness is derived from $M_{\phi-\phi}$ curve
 k_s shear stiffness is derived from $V-q$ curve
 v_i transverse displacement of the i^{th} boundary
 ϕ_i rotation of the i^{th} boundary
 v_{i+1} transverse displacement of the $(i+1)^{\text{th}}$ boundary
 ϕ_{i+1} rotation of the $(i+1)^{\text{th}}$ boundary.

This macro element can be easily extended to a plane type by adding two more states: a normal and a bending state for the vertical direction. Thus, five independent states: Two macro bending (positive bending and negative bending), two normal (tension and compression) and one macro shear state, and their interactions describe the full state of a region that may represent a plane beam-to-column connection in a composite frame as illustrated in Figure 4.3.

To demonstrate this powerful scaling technique, [Dorka and Amorntipsakul, 2008] also developed a beam-type macro element by utilising the Innsbruck component model for beam-to-column connections. From the obtained results it was concluded that the problem of including local behaviour in beam-to-column connections in a global analysis could be scaled in a mechanically consistent manner by using the macro element approach without loss of accuracy.

4.2 Scaling of plane beam-to-column connections

To fully utilise the accuracy and resolution of local finite element modelling in higher frame analysis, a scaling method is needed that correctly maps the performance of a detailed FE model on a macro element that represents the whole connection region during the frame analysis.

[Dorka, 2009] explained the concept of scaling method in his paper. Mechanically consistent scaling requires the definition of a complete set of orthogonal boundary states for a macroscopic region. Each orthogonal state consists of a set of boundary deformations and associated forces which are represented by only two variables, i.e. a deformation and a force. They are given for a plane rectangular macro element in Figure 4.4 where five states

Figure 4.3: Possible modification of component model from Innsbruck component model to represent a plane beam-column connection as macro element with orthogonal boundary states: 2 normal, 2 bending and 1 shear state [Dorka and Amorntipsakul, 2008]

are sufficient to present all possible states by linear combination. Being of beam-type, there are two normal states defined by $\delta_x - N_x$ and $\delta_y - N_y$, two bending states defined by $\phi_x - M_x$ and $\phi_y - M_y$ and a shear state defined by $\gamma - M_\gamma$. These ‘*beam-like*’ boundaries are very useful when it comes to defining macro elements for beam-to-column connections, since these can be directly coupled to regular beam elements. To describe all possible states under the condition of straight boundaries (beam continuity conditions), minimum eight degrees of freedom which come from two nodal displacements for each corner are used (see Figure 4.4).

Orthogonality stipulates that the work done on each state is independent of the work done on the other states. Because of this, single nonlinear force-deformation relationships exist in general for each state, i.e. $\delta_x - N_x$, $\delta_y - N_y$, $\phi_x - M_x$, $\phi_y - M_y$ and $\gamma - M_\gamma$ for a plane rectangular element, with their coupling described in the force space. This type of constitutive relation can be represented by single functions for each forcedisplacement relationship and a surface model in the force space. Hence, a five-dimensional surface law is required in general to fully describe the constitutive relationship for a plane rectangular macro element.

To reduce dimensions of the surface law some basic assumptions may be made for typical beam-to-column connection regions:

- Normal forces in the beams may have little effect on the joint connection and thus may be neglected in the law. This reduces the law to four dimensions.
- The two bending states $\phi_x - M_x$ and $\phi_y - M_y$ hardly use the same components in the region for their load transfer, therefore they may be considered without mutual interaction. This leads to two independent three-dimensional laws: $N_y - M_\gamma - M_x$ and $N_y - M_\gamma - M_y$.
- Bilinear approximations for the $\phi_x - M_x$, $\phi_y - M_y$ and $\gamma - M_\gamma$ relationships, which gives two-surface models for $M_x - M_\gamma$ and $M_y - M_\gamma$, may be used. Each has a yield and a failure surface that depends on N_y .

With these assumptions, only two three-dimensional interactions, which can be represented in plane by using the column normal force N_y as a parameter for the curves, macro states are left (see Figure 4.5).

A weak beam-strong column concept is frequently used so that the column remains elastic and a $M_y - M_\gamma$ interaction is not required. With this, only the $M_x - M_\gamma$ (macro beam bending and macro shear states) must be developed with the local finite element model.

The stiffness matrix of a ‘beam-type’ macro element excluding the normal state is also given by [Dorka, 2009]:

$$k_\gamma \mathbf{TU} = \mathbf{F} \quad (4.6)$$

with:

Figure 4.4: Orthogonal boundary states for a beam-to-column connection region and definition of DOFs [Dorka, 2009]

Figure 4.5: Simplified surface model for a beam-to-column connection [Dorka, 2009]

$$\begin{aligned}
 \mathbf{T} &= \begin{bmatrix} \frac{1}{4} & \frac{1}{2}h_y & -\frac{1}{4} & \frac{1}{2}h_y & \frac{1}{4} & -\frac{1}{2}h_x & -\frac{1}{4} & -\frac{1}{2}h_x \\ \frac{1}{2}h_y & \frac{1+k_x^*}{4l_y^2} & -\frac{1}{2}h_y & \frac{1-k_x^*}{4l_y^2} & \frac{1}{2}h_y & -h_{xy} & -\frac{1}{2}h_y & -h_{xy} \\ -\frac{1}{4} & -\frac{1}{2}h_y & \frac{1}{4} & \frac{1}{2}h_y & -\frac{1}{4} & \frac{1}{2}h_x & \frac{1}{4} & \frac{1}{2}h_x \\ \frac{1}{2}h_y & \frac{1-k_x^*}{4l_y^2} & -\frac{1}{2}h_y & \frac{1+k_x^*}{4l_y^2} & \frac{1}{2}h_y & -h_{xy} & -\frac{1}{2}h_y & -h_{xy} \\ \frac{1}{4} & \frac{1}{2}h_y & -\frac{1}{4} & \frac{1}{2}h_y & \frac{1}{4} & -\frac{1}{2}h_x & -\frac{1}{4} & -\frac{1}{2}h_x \\ -\frac{1}{2}h_x & -h_{xy} & \frac{1}{2}h_x & -h_{xy} & -\frac{1}{2}h_x & \frac{1+k_y^*}{4l_x^2} & \frac{1}{2}h_x & \frac{1+k_y^*}{4l_x^2} \\ -\frac{1}{4} & -\frac{1}{2}h_y & \frac{1}{4} & -\frac{1}{2}h_y & -\frac{1}{4} & \frac{1}{2}h_x & \frac{1}{4} & \frac{1}{2}h_x \\ -\frac{1}{2}h_x & -h_{xy} & \frac{1}{2}h_x & -h_{xy} & -\frac{1}{2}h_x & \frac{1+k_y^*}{4l_x^2} & \frac{1}{2}h_x & \frac{1+k_y^*}{4l_x^2} \end{bmatrix} \\
 \mathbf{U} &= [u_1 \ u_2 \ u_3 \ u_4 \ u_5 \ u_6 \ u_7 \ u_8]^T \\
 \mathbf{F} &= [F_1 \ F_2 \ F_3 \ F_4 \ F_5 \ F_6 \ F_7 \ F_8]^T
 \end{aligned}$$

$h_x = \frac{1}{l_x}$, $h_{xy} = \frac{1}{l_x l_y}$, $h_y = \frac{1}{l_y}$, $k_x^* = \frac{k_{bx}}{k_\gamma}$, $k_y^* = \frac{k_{by}}{k_\gamma}$ and degrees of freedom according to Figure 4.4

where l_x length of element along X axis
 l_y length of element along Y axis
 k_{bx} bending stiffness of element as defined in Figure 4.4
 k_{by} bending stiffness of element as defined in Figure 4.4
 k_γ shear stiffness of element.

The constitutive relationships, surface laws and flow rules need to be determined using a local FE model. They are used to define the properties of a macro element before it is implemented in an analysis. This macro element can then be included in a regular frame analysis greatly improving its accuracy. The surface laws and flow rules may be used again

after an analysis by applying selected states to analyse internal stresses and failures. Hence, the problem is scaled with considerable reduction of implementation and numerical effort on the higher scale without loss of accuracy and the capacity of retrieving local behaviour at any point of the analysis.

Chapter 5

Motivation and objective

Past research in steel-concrete beam-to-column connections focused on the development of design procedures and criteria. In Europe, this work was driven by the effort to develop Eurocode 4. During the course of this work, two important aspects became apparent:

1. Detailed local models were required to assess the importance of local limit states, like the rupture of welds, bolts or reinforcement or the buckling of flanges and webs. And it leads to the application of finite elements because of their rapidly increasing level of sophistication and ease of application in user-friendly programs.
2. Because of economic reasons, the majority of beam-to-column connections are semi-rigid and partial strength. A good representation of the limit states and the stiffness are required and both have to be included in the frame analysis because both may lead to redistribution of internal forces and moments, and any local connection failure may initiate global failure.

This requires a modelling approach, which is capable of modelling local behaviour and transfer it to the next level: a frame analysis. Thus, mechanically consistent scaling as has been developed by [Dorka, 1991, Dorka, 2009] provides a rational frame work to perform a non-linear composite frame analysis efficiently without losing any local information on failures. What is needed is a sophisticated local FE model of a composite connection region that is capable of providing the required macro constitutive relations in ‘virtual tests’, and also allows ‘back-scaling’ of frame results to local behaviour.

It is the purpose of this work to develop such a local model for welded composite beam-to-column connections and validate its application for mechanically consistent scaling.

Chapter 6

Numerical modelling

A finite element model for mechanically consistent scaling of welded beam-to-column composite connections is developed and described in this chapter. This model is subjected to five orthogonal boundary states as shown in Figure 4.4 that are sufficient to present all possible macro states by linear combination. Proper boundary conditions and loading is developed to perform virtual tests on this model within the concept of scaled frame analysis. Generic programming is applied to arbitrarily generate any geometries of welded composite connections without difficulties.

6.1 Generic geometry

In practice many types of moment resisting composite beam-to-column connections can be used in braced and/or un-braced frames [Bode, 1998]. The cruciform welded beam-to-column composite connection with solid slab (see the left part of Figure 6.1) is investigated in this study. The steel beam is welded to a steel column and fully connected to the solid reinforced concrete slab with shear connectors in order to obtain composite behaviour. The section of steel beam studied here is ‘*I*’ or ‘*Wide Flange*’ section and the section of steel column is ‘*H*’ section.

As shown in Figure 6.1, a welded composite connection is composed of:

- Steel beams
- Steel column
- Stiffeners
- Reinforced concrete slabs
- Welds
- Shear connectors

Figure 6.1: Welded beam-to-column composite connection and its components [Bode, 1998]

Figure 6.2: Finite element local model for virtual testing of composite joint with welded connection showing all relevant components

Parameters	Example 1 (mm)	Example 2 (mm)
Beam width	140	100
Beam depth	133	200
Flange thickness of beam	8.5	8.5
Web thickness of beam	5.5	5.6
Root radius of beam	12	12
Column width	160	120
Column depth	160	120
Flange thickness of column	13	11
Web thickness of column	8	6.5
Root radius of column	15	12
Leg size of welding	3	4
Concrete thickness	100	120
Concrete covering from top surface	25	60
Concrete covering from side surface	25	30
Effective width of slab	1500	600
Crack spacing	100	150

Table 6.1: Geometric input to generic model creating the two examples of Figure 6.3

In this study, a finite element model that can be subjected to 5 independent macro states is developed and proposed as shown in Figure 6.2. Meshing of this model and nodes will depend on geometry of the connection itself. It is exemplified in Table 6.1 and Figure 6.3. Full composite behaviour is assumed, because slip between reinforced concrete slabs and steel beams is prevented by column flanges. Thus, shear connectors are not modelled (see Figure 6.2). If the need arises, this model can accommodate them by introducing shear springs between concrete slab and steel beam to represent their slip behaviour. To ensure Bernoulli conditions, end plates are added at both ends of the beams.

SLang (Structural Language Version 5.1.0) developed by [Bucher et al., 2006] at Weimar University is used as a tool in this study. The composite beam-to-column connection is meshed in three dimensions. In order to validate the FE local model, generic programming is proposed. With generic programming, users need not to develop a new model all the time. Generic programming will help users to generate this finite element local model under any circumstances.

The local nodes will be defined by geometry of the connection and location of cracks. The group of basic variables, such as geometric properties of steel beam, steel column, concrete slab and crack spacing, has to be provided. This numerical model can be used as a virtual specimen to develop properties of macro elements and to be used in scaling according to Chapter 4. Therefore, this virtual specimen also needs to fit into a beam model in frame analysis.

Generic programming is very important for generating such a virtual specimen. Two

Figure 6.3: Two instances of virtual specimen generated with the generic model

finite element models with different geometries are generated below as demonstration. The group of parameters shown in Table 6.1, i.e. geometric properties of the beam, column and concrete slab has to be provided. In Figure 6.3, two examples of resulting finite element models from bottom view, one with a stocky geometry and another one with a slim geometry are presented demonstrating a broad spectrum of application for this generic model.

6.2 Boundary conditions

To perform a virtual test the boundary conditions corresponding to the loading must be defined properly. It is important that the deformations of beam-type boundaries occurring from the loads acting at the end of the beams to represent each independent state must not be prevented by these boundary conditions. And since there are a large number of degrees of freedom in the model, advantage of symmetry in the connection should be taken in order to reduce its number of degrees of freedom. Only half of the connection along the composite beam web axis as illustrated in Figure 6.2 is modelled.

In this study, the restraints shown in Figure 6.4 are used to simulate real test situations. The horizontal and vertical displacements in the middle of the column base are restrained and the horizontal displacements in the middle of the upper part of the column are prevented. These bearings must be free of forces for each independent state because of equilibrium of independent states. And as a consequence of the symmetry condition all lateral translations of the connection will be always restrained in the plane of symmetry.

The applied macro states, i.e. bending, shear and combined states, are investigated. Loads are distributed linearly to reflect standard beam end conditions (see Figures 6.5 and 6.6). Vertical loads are also given for the macro shear state as shown in Figure 6.6 for equilibrium reasons. For combined states, horizontal forces from macro bending and

Figure 6.4: Restraints used in this study

Figure 6.5: Linearly distributed loads applied at both ends of the virtual specimen to represent the macro bending state

horizontal forces accompanying with vertical forces from macro shear will be added together to analyse combined behaviour.

6.3 Element types and material properties

6.3.1 Steel elements and weld elements

Solid eight node brick elements in Figure 6.7 are utilised to model steel beams, steel column and welds. Mises kinematic hardening material laws illustrated in Figure 6.8 are defined for steel components and linear elastic law is defined for welds. Steel properties required in SLang consist of Young's modulus, Poisson's ratio, mass density, yield stress and hardening modulus. Yield stress and hardening modulus depend on the grade of steel.

Figure 6.6: Horizontal linearly distributed loads with vertical loads applied at both ends of the virtual specimen to represent the macro shear state

Figure 6.7: Eight-node brick element in SLang [Bucher et al., 2006]

Figure 6.8: Mises kinematic hardening material law for brick elements representing steel components

6.3.2 Concrete elements

Solid eight node brick elements with kinematic hardening material laws are also used to model concrete elements.

As already discussed in Chapter 3, [Leon et al., 1996] also developed a finite element model. To avoid convergence problems resulting from sharply softening tensile stress-strain curve for tension in slabs, they assumed elastic-perfectly plastic behaviour, rather than strain softening, after the concrete reached its compressive strength. Consequently, elastic-perfectly plastic behaviour for concrete slab is also assumed in this study. The cylinder compressive strength of concrete is input as yield strength with hardening modulus equal to zero. Young's modulus depends on the compressive strength of concrete and Poissons ratio of concrete is 0.20.

6.3.3 Crack elements

Creep and shrinkage effect of concrete slab are neglected in this work because only short-term loading is considered here.

[Hanswille, 1996] studied the crack formation of reinforced concrete members in tension that can be applied to composite concrete-steel beams and connections. He explained that there are four states in idealised load deformation behaviour of a concrete member in tension as illustrated in Figure 6.9. The first one is un-cracked section in state A. Under this state, deformations and stresses, including effects of shrinkage, can be calculated by fundamental elastic theory. After reaching the tensile strength of concrete, further increase of the load in state B causes cracks and thus the deformations increase rapidly. This type of cracking is defined as initial crack. In state C the number of cracks does not increase significantly. The bond between cracks reduces the maximum strain of the reinforcement at the crack locations and causes the tension stiffening effect of concrete between cracks. This state of cracking is defined as stabilised crack formation. The last state D is post-

Figure 6.9: Idealised load deformation behaviour of a reinforced concrete member in tension [Hanswille, 1996]

yielding state. It is influenced by local bond failure at the crack locations, the elongation of reinforcement at the maximum load and the ratio of tensile strength to yield strength of the reinforcement. Figure 6.10 shows distribution of strains in the case of single and stabilized crack formation studied by Hanswille.

In this study, contact springs and bilinear spring elements are implemented to model cracks in slabs. The contact spring elements that are able to transfer only compression forces are added at every node at regular intervals. When cracks are closed and under compression, these contact spring elements have a stiffness equal to the slab. When cracks are open and under tension, the stiffness accounts for the reinforcement and tension-stiffening effect of the surrounding concrete.

To derive the locations of these springs, average crack spacing has to be pre-calculated to identify the crack locations in the concrete slab. The prediction formulae of crack spacing in reinforced concrete proposed by [Piyasena et al., 2004] are referred in this work. They state that the most important parameters affecting spacing and width of cracks are found to be steel stress at the cracked section f_s , effective width of the member per one bar (b/m), clear concrete cover c , bar diameter ϕ , and the effective depth d (only if $d < 300$ mm). Equation 6.1 is the empirical formula for evaluating critical crack spacing in beams with $d \geq 300$ mm.

$$l_c = \left(\frac{200}{f_s} + 0.5 \right) l_f \quad (6.1)$$

Figure 6.10: Distribution of strains in the case of single and stabilized crack formation [Hanswille, 1996]

where f_s is steel stress at the cracked section in MPa and l_c is critical crack spacing in mm.

The value of l_f in mm in the above equation is calculated using the following formula.

$$l_f = 9e' + (0.65 + 0.35e')(\phi - 10) \quad \text{if } \phi > 10 \text{ mm} \quad (6.2)$$

or

$$l_f = 9e' \quad \text{if } \phi \leq 10 \text{ mm} \quad (6.3)$$

where ϕ is the bar diameter in mm and

$$e' = (0.8 + 0.2c')e \quad (6.4)$$

with

$$c' = c/\phi \quad (6.5)$$

$$e = b/(m\phi) \quad (6.6)$$

where m is number of reinforcing bars.

For slabs with $d < 300$ mm they multiplied the same formula by a factor in Equation 6.7.

$$F_{cs} = 1.1 - \frac{c'}{6 + 0.22d} \leq 1 \quad (6.7)$$

where d is in mm.

It is noted that the crack spacing in this model could be re-calculated later following any state of the art in new prediction of crack to improve this model. Figure 6.11 shows the material law for these spring elements.

To model the reinforcing bars the spring elements with bilinear material law (see Figure 6.12) are implemented. Springs representing reinforcement bars are added at the

Figure 6.11: Constitutive law for spring elements representing cracked regions

Figure 6.12: Bilinear material law for crack elements

position of reinforcement in the cracks. The tension stiffening effect is also taken into consideration and included in these springs.

The parameters for this element are derived from the idealised load deformation behaviour of a concrete member in tension with stabilised crack formation by [Hanswille, 1996]. The deformation of these springs are directly related to the strains in the reinforcement and thus to reinforcement failure.

$$\varepsilon_{sm} = \varepsilon_{s2} - \beta_t(\varepsilon_{sr2} - \varepsilon_{sr1}) \quad (6.8)$$

$$\varepsilon_{sm} = \varepsilon_{sy} - \beta_t(\varepsilon_{sr2} - \varepsilon_{sr1}) + \delta \left(1 - \frac{\sigma_{sr1}}{f_{sk}} \right) (\varepsilon_{s2} - \varepsilon_{sy}) \quad (6.9)$$

with

ε_{sm}	mean strain of reinforcement between cracks
ε_{sy}	strain of reinforcement at the yield point
ε_{s2}	strain of reinforcement (without concrete)
ε_{sr1}	strain of reinforcement before initial crack
ε_{sr2}	strain of reinforcement when stabilised crack formation begins
σ_{sr1}	stress of reinforcement before initial crack
f_{sk}	yield stress of reinforcement
$\beta_t = 0.4$	for short term loading
$\delta = 0.8$	when deformed reinforcing bar provided the ratio of tensile strength to yield strength is higher than 1.08 and the characteristic elongation at maximum loads exceeds 5%.

6.4 Limit state

6.4.1 Global plastic limit state

Only, if a considerable deviation from linear behaviour is observed, a global yield surface can be defined. Thus, two per cent deviation from elastic unloading as presented in Figure 6.13 is defined as global yield point in this study.

6.4.2 Failure states

Local failures that are included in the model are:

- Buckling of column web panel
- Buckling of beam flange in compression
- Weld rupture
- Fracture of slab reinforcement in tension
- Crushing failure of concrete slab against column

Figure 6.13: Yield point defined in this study

6.4.2.1 Buckling of plate elements

This FE model cannot analyse plastic buckling because large deformations are not included. Also, imperfections must be taken into consideration as well as residual stresses. This requires a statistical evaluation of the results, which has been performed already to back-up design curves for buckling in modern codes. Therefore, the criteria for buckling failure are taken from the relevant literature.

Introduction

Figure 6.14 shows local buckling of an I-section column that was built up from slender-plate elements. In Figure 6.15 it can be observed that the member from slender-plate elements may fail prematurely due to local buckling, as indicated by the reduction from the full line to the dashed line. A slender-plate element does not fail by elastic buckling, but exhibits significant post-buckling behaviour, as shown in Figure 6.16. Because of this, the plate's resistance to local failure depends not only on its slenderness, but also on its yield strength and residual stresses, as shown in Figure 6.17. The resistance of a plate element of intermediate slenderness is also influenced significantly by its geometrical imperfections, while the resistance of a stocky-plate element depends primarily on its yield stress and strain-hardening moduli of elasticity, as indicated in Figure 6.17.

Effects of initial curvature and residual stresses

Real plates are not perfectly flat, but have a small initial curvature and this causes them to deflect transversely as soon as they are loaded, as shown in Figure 6.16. These

Figure 6.14: Local buckling of an I-section column [Trahair et al., 2008]

Figure 6.15: Effects of local buckling on the resistances of compression member [Trahair et al., 2008]

Figure 6.16: Post-buckling behaviour of thin plates [Trahair et al., 2008]

Figure 6.17: Ultimate strength of plates in compression [Trahair et al., 2008]

Figure 6.18: Simply supported plate under bending and shear

deflections increase rapidly as the elastic buckling stress is approached, but slow down beyond the buckling stress and approach those of an initially flat plate.

In a thin plate with initial curvature, the first yield and failure occur only slightly before they do in a flat plate, as indicated in Figure 6.16, whereas the initial curvature has little effect on the resistance of a thick plate (see Figure 6.17). Only in a plate of intermediate slenderness, the initial curvature causes a significant reduction in the resistance, as can be concluded from Figure 6.17.

Real plates usually have residual stresses induced by uneven cooling after rolling or welding. Residual compressive stresses cause it to buckle prematurely and reduce its ultimate strength, as shown in Figure 6.17. Residual stresses also cause premature yielding in plates of intermediate slenderness, as indicated in Figure 6.17, but have a negligible effect on the strain hardening buckling of stocky plates.

Plate elements under bending and shear

Figure 6.18 represents a simply supported flat plate subjected to combined bending and shear. α represents the relationship between length and width and ψ represents the stress relationship between σ_2 and σ_1 , where σ_1 is the maximum compressive stress at the edge of the plate.

$$\alpha = a/b \quad (6.10)$$

$$\psi = \sigma_2/\sigma_1 \quad (6.11)$$

[Klöppel and Scheer, 1960] studied the local buckling behaviour of plate elements in different situation and developed various practical diagrams in order to calculate buckling stress that are widely used in Germany nowadays. [Petersen, 2013] also referred to [Klöppel and Scheer, 1960] and [Scheer, 1998] for defining ultimate buckling stresses in his textbook.

Figure 6.19 shows the relationship between k_σ (buckling coefficient for bending) and α for each ψ parameter. For unstiffened rectangular plate elements under linear distributed

Figure 6.19: Buckling coefficient for pure bending [Klöppel and Scheer, 1960]

stresses, k_σ can be obtained from this diagram, when α and ψ are known and the buckling stress for the pure bending case can be calculated.

$$\sigma_{1Ki} = k_\sigma \cdot \sigma_e \quad (6.12)$$

$$\sigma_e = \frac{\pi^2 E}{12(1 - \mu^2)} \left(\frac{t}{b} \right)^2 \quad (6.13)$$

E is Young's modulus. μ is Poisson's ratio equal to 0.3 for steel and t is the thickness of the plate.

In the pure shear case, the buckling stress can be calculated as:

$$\tau_{Ki} = k_\tau \cdot \sigma_e \quad (6.14)$$

k_τ can be obtained from Figure 6.20 by means of the equations in the figure.

The ideal basic assumptions, for example ideal material behaviour, ideal isotropic material, ideal flat plate without residual stresses, cannot be fulfilled in practice. Because of these reasons and all imperfections in form of initial curvature from rolling or welding process and residual stresses from welding, reduction factors are needed.

The proof of buckling safety for an unstiffened rectangular plate element with simple support under bending and shear stress referred to [Scheer, 1998], is presented as follows

Figure 6.20: Buckling coefficient for pure shear [Klöppel and Scheer, 1960]

- Critical slenderness ratio

$$\lambda_a = \pi \sqrt{\frac{E}{f_{y,k}}} \quad (6.15)$$

where $f_{y,k}$ is yield strength.

- Ideal buckling stresses and slenderness ratio of plate

For bending,

$$\sigma_{xPi} = k_{\sigma_x} \cdot \sigma_e \quad (6.16)$$

$$\lambda_{P\sigma_x} = \pi \sqrt{\frac{E}{\sigma_{xPi}}} \quad (6.17)$$

For shear,

$$\tau_{Pi} = k_\tau \cdot \sigma_e \quad (6.18)$$

$$\lambda_{P\tau} = \pi \sqrt{\frac{E}{\tau_{Pi}\sqrt{3}}} \quad (6.19)$$

- Slenderness ratio of plate, corresponding reduction factors and ultimate buckling strength

For bending,

$$\lambda'_{P\sigma_x} = \frac{\lambda_{P\sigma_x}}{\lambda_a} = \sqrt{\frac{f_{y,k}}{\sigma_x P i}} \quad (6.20)$$

$$k_{\sigma_x} = c \left(\frac{1}{\lambda'_{P\sigma_x}} - \frac{0.22}{\lambda'^2_{P\sigma_x}} \right) \leq 1 \quad (6.21)$$

$$c = 1.25 - 0.25\psi \leq 1.25 \quad (6.22)$$

$$\sigma_{xP,R,d} = k_{\sigma_x} \cdot \frac{f_{y,k}}{\gamma_M} \quad (6.23)$$

For shear,

$$\lambda'_{P\tau} = \frac{\lambda_{P\tau}}{\lambda_a} = \sqrt{\frac{f_{y,k}}{\tau_{Pi} \sqrt{3}}} \quad (6.24)$$

$$k_{\tau} = \frac{0.84}{\lambda'_{P\tau}} \leq 1 \quad (6.25)$$

$$\tau_{P,R,d} = k_{\tau} \cdot \frac{f_{y,k}}{\sqrt{3} \cdot \gamma_M} \quad (6.26)$$

For design purpose, γ_M is the safety factor and equal to 1.1. But this safety factor is set to 1.0 for defining ultimate buckling stress in this study.

- Interaction behaviour between $\sigma_{xP,R,d}$ and $\tau_{P,R,d}$

$$\left(\frac{\sigma_x}{\sigma_{xP,R,d}} \right)^{1+k_{\sigma_x}^4} + \left(\frac{\tau}{\tau_{P,R,d}} \right)^{1+k_{\sigma_x} \cdot k_{\tau}^2} \leq 1 \quad (6.27)$$

The interaction behaviour between bending and shear from Equation 6.27 must be checked to analyse the ultimate buckling safety of a plate.

When this mode of failure occurs in some regions of a connection, increasing loads can be mostly redistributed to other connection regions. It means that such connections have some reserve strength and can take additional loads before collapsing.

Plate elements under compression

In some failure modes, e.g. buckling of beam flange, buckling due to compression only can occur. Buckling behaviour of a plate element under compression has the same basic background that is already discussed. The buckling stress can be calculated from Equation 6.28. And the buckling coefficient k can be obtained from the diagram in Figure 6.21. Again, due to imperfections and residual stresses, a reduction factor is calculated from Equation 6.21.

$$\sigma_{1Ki} = k \cdot \sigma_e \quad (6.28)$$

Figure 6.21: Buckling coefficient for plate element under compression [Klöppel and Scheer, 1960]

6.4.2.2 Weld rupture

A defect in a weld may lead to premature weld failure, which must be excluded by inspection. Therefore no common defects, e.g. incomplete fusion, incomplete penetration, porosity, inclusion of slag, undercutting etc. [Blodgett, 1966] are considered here.

Test results for welded joints subjected to out-of-plane bending carried out by Picard and Beaulieu [Picard and Werren, 1984] were collected and presented by [Gomez et al., 2008]. Equivalent stresses from bending stresses and shear stresses were calculated in this dissertation in order to find the ultimate strength of a weld from test results. The test results from Picard and Beaulieu were selected here because there were enough specimen close to the investigated situation in this research. Figure 6.22 shows their test specimen. In accordance with these test results, the average ultimate strength of a weld is 2.10 times higher than the yield strength of the base metal.

From their test results, ultimate strains of welds were not presented. In this study, rupture stress is defined as two times the yield strength of the base metal, i.e. 710 MPa. The other required properties of the weld are the same as steel.

Welds typically fail in a brittle manner. They do not exhibit much plastic deformation. Weld rupture occurs shortly after it yields. Hence, a primarily linear relationship between rupture stress and strain is assumed. When weld rupture occurs in some areas, the crack will propagate. Thus, initial weld rupture is considered as failure of the model.

6.4.2.3 Reinforcement fracture

Crack formation of concrete in tension was already explained in this chapter. It is a fact that when the strain of reinforcement in a crack is equal to the ultimate strain of the

Figure 6.22: Fillet weld connection loaded eccentrically out-of-plane [Picard and Werren, 1984]

reinforcing bar, the rupture of reinforcing bar happens. And the strain of the reinforcement in the crack is related to the crack width. Consequently, the crack width is used to define reinforcement rupture in this study. This kind of failure is also a sudden failure.

In Figure 6.23, [Kreller, 1991] proposed many relationships between strain of reinforcement in a crack (ε_{sr}) and mean strain of reinforcement (ε_{sm}). These relationships depend on many factors, e.g. reinforcement ratio, strength of concrete and type of reinforcing bar. The crack width at reinforcement rupture can be calculated once the mean strain of reinforcement is obtained.

6.4.2.4 Crushing of concrete slab

This local failure mode is a brittle failure. It can be defined by the standard two-surface model given in Figure 6.24. When it reaches the compressive strength of the concrete, failure occurs. This is also an abrupt failure.

Figure 6.23: Relationship between strain of reinforcement in a crack and mean strain of reinforcement [Kreller, 1991]

Figure 6.24: Standard two-surface model for concrete [Horrigmoe et al., 2007]

Chapter 7

Validation

Any numerical models should not be accepted, until they are verified. For this reason the finite element local model developed in this research must be validated against testing results. In this chapter the validation of the finite element model is presented and discussed. The test results from [Ramm and Elz, 1996] performed at University of Kaiserslautern are used for this purpose.

7.1 Tests at University of Kaiserslautern

[Ramm and Elz, 1996] carried out experimental investigations and parameter studies at University of Kaiserslautern in order to investigate the influence of reinforcement on the development of cracks and the behaviour of composite slabs as part of composite beams in negative bending areas. In negative moment areas of composite beams, i.e. concrete slabs under tension, the longitudinal reinforcement strongly influences the contribution of the concrete slab to the load bearing behaviour of the cross section. The longitudinal reinforcement must adequately limit the width of the cracks under service load. And the longitudinal reinforcement can fail early, if the cross section of the reinforcement is rather small.

The behaviour and the cracking of the tensioned concrete slab of composite beams are greatly influenced by the structural situation in regions with negative moments. The concrete flange of a continuous beam will show behaviour different from a beam with a connection to a column. Different forms of such connections with varying stiffness will lead to different behaviour of the concrete flange.

They conducted two series of tests. The first series were composite beams with a continuous concrete flange. And the second series were composite beam-to-column joints with cover plate and web plate connections. The proposed finite element local model in Chapter 6 will be applied and validated against results of the first test series. Figure 7.1 presents the test specimen of the first series.

To investigate the influence of uniformly distributed reinforcement on the crack pattern and on the load bearing capacity of the composite beams the percentage of reinforcement

Figure 7.1: Test specimen [Ramm and Elz, 1996]

was varied in this test. For validating the finite element model the results from the test with reinforcement ratio 0.4 percent are used. The length of the beams (6.0 m), the spacing of the transverse reinforcement (20 cm), the spacing between the shear connectors (15 cm), the diameter of shear studs (3/4 inch) and the width of concrete slab (2.0 m) were kept constant to exclude disturbing influences on the results, which may appear by varying these parameters.

[Ramm and Elz, 1996] explained the arrangement of their tests in their paper. Figure 7.2 shows the test arrangement for the test series. The tests consisted of the load-generating device that applied the load, the test specimen and the anchoring construction at the end of the specimen. The load was applied from the cylinder through the specimen by a longitudinal girder, the cross beam and the tie rods. The concrete flange was positioned on the upper side of the test beam for better observation of the crack widths.

They also discussed about the development of cracks in the first test series. The bending moment, under which the first cracks in the experiment occurred, reached only 90 per cent of the theoretical moment calculated with the tensile strength of the concrete. And this should be considered in calculating the minimum reinforcement. The authors concluded that the tensile strength of the concrete slab was reduced by the transverse reinforcement and in the region above the steel girder also by the studs. Thus, the crack development started under a rather low bending moment. Crack pattern at the end of the test with reinforcement ratio 0.4 per cent is shown in Figure 7.3. It is remarkable that the cracks coincided with the transverse reinforcement for this test.

In negative bending moment areas the concrete flange of a composite beam can be assumed as a concrete slab under pure tension. And the investigations of their own tensile tests on reinforced concrete slabs show that the ductility of the reinforced concrete slabs in the area of plastic deformation depends on the reinforcement ratio and the stress-strain behaviour of the reinforcement. They concluded that the stress-strain behaviour of the

Figure 7.2: Setup of the test series [Ramm and Elz, 1996]

Figure 7.3: Crack pattern at the end of the test with reinforcement ratio 0.4 percent [Ramm and Elz, 1996]

Figure 7.4: Finite element local model for validation

reinforcement has a direct influence on the plastic deformation of the reinforcing steel in the cracks. Increasing the ratio between the elastic limit and the tensile strength and higher values of elongation before reduction of area will lead to larger plastic deformability in the cracks.

7.2 Validation

In detailed finite element analysis, validated local models must be used. This refers to material models and components such as crack models etc. The next validation step is the global model. It may be inferred that, if the local modelling is correct, the global model that introduces only different geometries may also be correct but this should be demonstrated at least for a typical case by a large-scale experiment.

Accordingly, the proposed finite element local model has to be validated against the testing results already described above. The behaviour of the composite slab as part of composite beams in regions with negative bending moment is taken into consideration. The geometrical parameters as shown in Figure 7.1 are input. Structural steel S 355, concrete class C 25/30 and reinforcing bars BSt 420S are utilised in this validation. The reinforcement ratio is 0.4 per cent.

For validation purpose, the finite element model illustrated in Figure 7.4 was developed and generated based on the same concepts as described in Chapter 6. The calculated crack spacing did not coincide with the observed crack spacing, but was used in the model for reasons of comparison.

After giving the boundary conditions and applying the vertical load along the column flanges to simulate the test situation, the relationship between negative bending moment and rotation is obtained. The rotation in this test is different from the definition of rotation

Figure 7.5: Definition of rotation in the test

Figure 7.6: Deformed FE model

normally used and is given in Figure 7.5. The loading, boundary conditions and deformed structure of the finite element model are given in Figure 7.6.

As discussed in the previous chapter, physical limit states are considered in this finite element model. The relationships between strain of reinforcement at cracking and mean strain of reinforcement proposed by [Kreller, 1991] are used. As mentioned in Chapter 6, when the ultimate strain is known as the property of reinforcement, the mean strain can be extrapolated from Kreller's curves. Then the crack width at rupture of reinforcement can be obtained from this mean strain. Since the real crack spacing is different from crack spacing input in the model, the crack width used as limit state in the model must be modified with a factor. Here, when the crack width at reinforcement level reaches 0.742 mm, the reinforcement should fail by rupture.

Figure 7.7 compares the negative bending moment–rotation curves generated by the numerical model with the test results. The bending moment shown in the curves is normalised by the calculated plastic moment. From the test it was reported that the specimen failed by rupture of the reinforcement before the complete plastic state could be reached. This also occurs in the model at a smaller rotation. From the validation results the stiffness at the un-cracked state of the finite element model is slightly different from the stiffness of the specimen. The reason is the un-cracked behaviour is not included in the numerical model. The crack model is based on an already stabilised crack formation and without considering the effect of transverse reinforcement. The stiffness of the model after stabilised crack formation until yielding is quite close to the test results. It can be seen that not only the stiffness of the joint in linear behaviour, but also the yield point could be

Figure 7.7: Bending moment–rotation curves of the FE model compared to test the results

captured quite well by the model. The rotation at reinforcement rupture obtained from the test results were different from the one obtained from the numerical model. The FE model gives stiffer behaviour because crack spacing is longer than the real crack spacing in the specimen. It is noted that the theoretical ultimate plastic moment of the specimen could not be reached. [Ramm and Elz, 1996] gave the reason that the reinforcement ratio of the specimen in the test was lower than the minimum reinforcement.

It can be concluded that this numerical model can be used to represent the behaviour of a welded composite connection with adequate accuracy.

Chapter 8

Illustrative examples

In this chapter, how to apply the developed finite element local model is presented in two examples. In the first example the procedure of acquiring bending stiffness and shear stiffness of the finite element model required for macro element is demonstrated. The Two-surface law for the macro beam-shear state that is composed of yield surface and failure surface is gained. Then, the application of the macro element approach in a frame analysis is presented in the second example in order to demonstrate how this macro element can be applied in a practical manner.

8.1 Example 1: Development of a two-surface model

The objective of this example is to show how to obtain macro bending stiffness, shear stiffness and the two-surface law for a macro element from a finite element local model. In general, a five-dimensional surface law is needed to fully describe the constitutive relationship for a plane rectangular macro element. As already discussed in Chapter 4, certain assumptions may be made for typical beam-to-column connection regions and this can reduce the dimensions of the surface law to two three-dimensional interactions. By using the normal force in the column as a curve parameter, these two three-dimensional interactions can be represented in plane. Moreover, with a weak beam – strong column concept, only the interaction between bending and shear or $M_x - M_\gamma$ without the influence of the normal force must be investigated. Therefore, only one two-surface law is developed. To obtain this law, $M_x - \phi_x$ and $M_\gamma - \gamma$ relationships are investigated and evaluated for their yield points and their limit states. The initial and post-yield stiffness for both relationships provide the stiffness coefficients in the respective matrix of the macro element.

Figure 8.1 shows the welded beam-to-column connection investigated. The connection consists of beam type 254x102 UB25 and column type 203x203 UC46. The reinforcement ratio is 1 per cent and the reinforcement diameter is 10 mm. The geometry of the connection and the materials used are given in Table 8.1 and Table 8.2, respectively. The finite element local model for this example is generated by generic programming (see Chapter 6) and is given in Figure 8.2.

Figure 8.1: Investigated welded beam-to-column connection

Parameters	Example 1 (mm)
Beam width	102
Beam depth	257
Flange thickness of beam	8.4
Web thickness of beam	6
Root radius of beam	7.6
Column width	203
Column depth	203
Flange thickness of column	11
Web thickness of column	7.2
Root radius of column	10.2
Leg size of welding	5
Concrete thickness	110
Concrete covering from top surface	55
Concrete covering from side surface	30
Effective width of slab	600
Crack spacing	137

Table 8.1: Geometry Example 1

Material	Types	E (MPa)	ν	σ_y (MPa)	σ_u (MPa)
Concrete	C 30/37	28300	0.2	300	300
Steel	S 355	210000	0.3	355	490
Reinforcing bar	BSt 420S	210000	-	420	500
Weld	-	210000	0.3	710	710

Table 8.2: Types of material and material parameters

Figure 8.2: Finite element local model for Example 1 to perform virtual tests

Virtual tests are performed according to Chapter 4 using the following combinations of macro bending and shear states:

- Case 1: M_x^+
- Case 2: M_x^-
- Case 3: M_γ
- Case 4: $0.7M_x^+ + 0.3M_\gamma$
- Case 5: $0.5M_x^+ + 0.5M_\gamma$
- Case 6: $0.3M_x^+ + 0.7M_\gamma$
- Case 7: $0.1M_x^+ + 0.9M_\gamma$
- Case 8: $0.7M_x^- + 0.3M_\gamma$
- Case 9: $0.5M_x^- + 0.5M_\gamma$
- Case 10: $0.3M_x^- + 0.7M_\gamma$

From these the global yield surface is defined and local failure modes (see Chapter 6) are used to identify the failure surface.

The following calculations will show that there is no buckling occurring at beam flanges and column web.

1. Buckling of beam flange under compression

The classification of beam flange will be checked based on Eurocode 3.

$$\begin{aligned} c &= \frac{b - t_w - 2 \cdot r}{2} = \frac{102 - 6 - 2 \cdot 7.6}{2} = 40.4mm \\ t_f &= 8.4mm \\ \frac{c}{f} &= \frac{40.4}{8.4} = 4.81 \end{aligned}$$

For $f_y = 355$ MPa; $\varepsilon = 0.81$

$$\frac{c}{f} = 4.81 \leq 9 \cdot \varepsilon = 7.29$$

This cross-section is Class 1: Plastic. There is no need to consider buckling of beam flange, because this cross-section can develop its full plasticity.

2. Buckling of column web under bending and shear

$$\begin{aligned} a &= 203 - 2(11 + 10.2) = 160.6mm \\ t &= 7.2mm \\ b &= 257 - 2(8.4 + 7.6) = 225mm \\ \alpha &= \frac{a}{b} = \frac{160.6}{225} = 0.714 \\ \psi &= 1.0 \\ \sigma_e &= \frac{\pi^2 E}{12(1 - \mu^2)} \left(\frac{t}{b} \right)^2 = 18980(7.2/225)^2 = 19.44kN/cm^2 \\ k_\sigma &= 4.5; \sigma_{ki} = 4.5 \cdot 19.44 = 87.48kN/cm^2 \\ k_\tau &= 12; \tau_{ki} = 12 \cdot 19.44 = 233.28kN/cm^2 \end{aligned}$$

• Bending

$$\begin{aligned} \lambda'_{P\sigma_x} &= \sqrt{\frac{f_{y,k}}{\sigma_{xPi}}} = \sqrt{35.5/87.5} = 0.637 \\ c &= 1.25 - 0.25\psi = 1.25 - 0.25 \cdot 1 = 1.0 \leq 1.25 \\ \kappa_{\sigma_x} &= c \left(\frac{1}{\lambda'_{P\sigma_x}} - \frac{0.22}{\lambda_{P\sigma_x}^2} \right) = 1.0 \cdot \left(\frac{1}{0.637} - \frac{0.22}{0.637^2} \right) = 1.57 - 0.54 = 1.03 \leq 1 \\ \sigma_{xP,R} &= f_y \end{aligned}$$

- Shear

$$\lambda'_{P\tau} = \sqrt{\frac{f_{y,k}}{\tau_{Pi}\sqrt{3}}} = \sqrt{35.5/(233.28 \cdot 1.73)} = 0.296$$

$$\kappa_{\tau} = \frac{0.84}{\lambda'_{P\tau}} = \frac{0.84}{0.296} = 2.84 \leq 1$$

$$\tau_{P,R} = \frac{f_y}{\sqrt{3}}$$

From the calculation, this column web section has full plastic capacity. It is emphasised when the modified slenderness ratio of the column web is plotted in the buckling curves as shown in Figure 8.3.

Figure 8.3: Modified slenderness ratio of column web plotted with buckling curves

Case 1: M_x^+

(a)

(b)

Figure 8.4: Case 1 (a) Von Mises Stress (b) $M_x - \phi_x$ relationship

Case 2: M_x^-

(a)

(b)

Figure 8.5: Case 2 (a) Von Mises Stress (b) $M_x - \phi_x$ relationship

Case 3: M_γ

(a)

(b)

Figure 8.6: Case 3 (a) Von Mises Stress (b) $M_\gamma - \gamma$ relationship

Case 4: $0.7M_x^+ + 0.3M_\gamma$

(a)

(b)

(c)

Figure 8.7: Case 4 (a) Von Mises Stress (b) $M_x - \phi_x$ relationship (c) $M_\gamma - \gamma$ relationship

Case 5: $0.5M_x^+ + 0.5M_\gamma$

(a)

(b)

(c)

Figure 8.8: Case 5 (a) Von Mises Stress (b) $M_x - \phi_x$ relationship (c) $M_\gamma - \gamma$ relationship

Case 6: $0.3M_x^+ + 0.7M_\gamma$

(a)

(b)

(c)

Figure 8.9: Case 6 (a) Von Mises Stress (b) $M_x - \phi_x$ relationship (c) $M_\gamma - \gamma$ relationship

Case 7: $0.1M_x^+ + 0.9M_\gamma$

(a)

(b)

(c)

Figure 8.10: Case 7 (a) Von Mises Stress (b) $M_x - \phi_x$ relationship (c) $M_\gamma - \gamma$ relationship

Case 8: $0.7M_x^- + 0.3M_\gamma$

Figure 8.11: Case 8 (a) Von Mises Stress (b) $M_x - \phi_x$ relationship (c) $M_\gamma - \gamma$ relationship

Case 9: $0.5M_x^- + 0.5M_\gamma$

(a)

(b)

(c)

Figure 8.12: Case 9 (a) Von Mises Stress (b) $M_x - \phi_x$ relationship (c) $M_\gamma - \gamma$ relationship

Case 10: $0.3M_x^- + 0.7M_\gamma$

(a)

(b)

(c)

Figure 8.13: Case 10 (a) Von Mises Stress (b) $M_x - \phi_x$ relationship (c) $M_\gamma - \gamma$ relationship

Two-surface law

Figure 8.14: Two-surface law derived from local numerical model

A two-surface constitutive law is derived from the local numerical model. After plotting the yield points and failure points for every case, the two surfaces (Figure 8.14) are acquired.

8.2 Example 2: Macro element in frame analysis

The process of applying the macro element for scaling to plane beam-to-column connection regions in a frame analysis was demonstrated by [Dorka, 2009]. This example is recovered here to demonstrate how the macro element can be utilised in a frame analysis.

A two-storey two-bay frame with welded composite connections subjected to increasing horizontal loads as shown in Figure 8.15 is investigated here to illustrate this scaling process. By using generic programming, the global geometric parameters are input to automatically generate the model without the need to redefine the generic element mesh. To obtain the required macro bending stiffness, macro shear stiffness and two-surface constitutive law, the same procedure presented in the previous example is followed. Figure 8.16 shows the derived two-surface model of this connection region.

Figure 8.15: Composite frame with welded connections [Dorka, 2009]

Figure 8.16: Two-surface constitutive law for the macro elements that model the connection regions [Dorka, 2009]

Figure 8.17: Element types in frame analysis [Dorka, 2009]

The frame model given in Figure 8.17 was analysed using SLang. The macro element of beam-type in the corners represents the scaled finite element model. Simple beam elements are utilised for each column and beam. Figure 8.18 shows the deformed structure from a SLang analysis.

Figure 8.18: Deformed frame from analysis in SLang

Figure 8.19: Load paths of each corner [Dorka, 2009]

In Figure 8.19 the load paths of each corner due to increasing loads are plotted. Whenever the load path reaches the yield surface, the stiffness of that corner will be changed from initial stiffness to post-yield stiffness. The results show that the central corner 3 and corner 4 show nonlinear behaviour since their load paths go beyond the yield surface. It can be observed that the central corners chiefly act in macro shear whereas the outer corners exhibit combined macro bending and shear. Corner 3 reaches the failure surface, which marks the end of the analysis.

Applying the load path of corner 3 to the local finite element model in a back-scaling process shows excessive straining of the brittle weld and large cracking of the right concrete slab (see Figure 8.20). Furthermore, the high uniform state of yielding taking place in the corner web is also observed.

Figure 8.20: Strain of central corner 3 close to weld rupture [Dorka, 2009]

Chapter 9

Summary and conclusions

The analysis of composite frames with semi-rigid, partial-strength connections requires the inclusion of local models in a global frame analysis. Therefore, simplifying component models have been proposed to be incorporated in a global analysis and are defined for composite connections in Eurocode 4. They are rather unwieldy due to a large number of parameters to be specified. In addition, a detailed representation of important local states, such as weld strains or plastic shear buckles in the web plate, is not possible. Moreover, they largely neglect the interaction with the column actions. On the other hand sophisticated local finite element models with thousands of degrees of freedom may represent local behaviour with good accuracy, but are not applicable in a regular practical frame analysis.

To include realistic local behaviour in a global analysis therefore requires mechanically consistent scaling as has been developed by [Dorka, 1991, Dorka, 2009]. This allows for the transfer of independent macro states between local and global models. Using this approach, local behaviour of beam-to-column connections can be included in a global analysis. Back-scaling from the macro level to the local finite element model recovers detailed local behaviour any time during the analysis.

It is the purpose of this work to develop such a local model for welded composite beam-to-column connections and validate its application for mechanically consistent scaling. Therefore, a detailed nonlinear finite element model using state of the art local modelling is developed. This sophisticated model does not increase the effort during frame analysis and design but leads to more realistic results and is open to new knowledge when it becomes available without changing the basic concept or practical application in a program. Thus, this finite element local model is a vital step in a mechanically consistent scaling process that broadcasts local effects to the next scale and preserves accuracy without influencing numerical efficiency of the analysis.

A generic FE model was developed that allows for a set of geometry inputs and can generate a particular finite element model for each instance without much effort. This generic model is flexible to include a new state of the art in local modelling any time. Developing a new finite element model by the user for every instance is avoided. In the future, such local models may become available to practicing engineers via the internet

to provide the required constitutive relationships for each instance of an application of a macro element in a frame analysis.

This FE model is verified against testing results conducted by [Ramm and Elz, 1996] at the University of Kaiserslautern. From the validation results it can be concluded that the results are satisfactory. Initial stiffness and yield strength can be well captured by this model. And the ultimate strength is close to the one calculated from theory. Because of differences in crack spacing between model and specimen, rotational capacity is slightly underestimated.

To demonstrate this powerful scaling technique, two illustrative examples are presented. In the first example, the procedure in finding the macro constitutive relationships, surface laws and flow rules using a local model in virtual tests is shown. The constitutive relationships obtained are used to define the properties of a macro element before it is implemented in a regular frame analysis. The application of such a macro element in global frame analysis is shown in the second example with considerable reduction of implementation and numerical effort on the higher scale. This is done without loss of accuracy and the capacity of retrieving local behaviour at any point of the analysis. From both examples the great potential of this generic finite element local model for mechanically consistent scaling is demonstrated.

For static loading an extension should be made to include the axial load in the column as a parameter for the surface law. In addition, modelling shear connectors as important components by using simple nonlinear spring elements should be considered. And other sophisticated finite element models for various typical beam-to-column connections should be developed with the same concept and validated against experimental results.

This approach also should be extended to cyclic loading. [Dorka, 2009] already gave some hints to cope with this. He suggested that hysteresis laws must be implemented instead of static force – displacement relationships and the prescribing surfaces must be allowed to change. Bilinear hysteresis laws which can be defined by a two-surface model with a kinematic hardening law should be used in a first approach. The same combinations of orthogonal states applying cyclic loading with increasing amplitudes can give such a hardening law. This should be adequate where stable plasticity governs the behaviour until failure, and cyclic deterioration can be neglected.

Bibliography

- [Ahmed et al., 1995] Ahmed, B., Li, T. Q., and Nethercot, D. A. (1995). Modelling composite connection response. In Bjorhovde, R., Colson, A., and Zandonini, R., editors, *Third International Workshop on Connections in Steel Structures: Behaviour, Strength and Design*, pages 259–268. Trento University.
- [Ahmed and Nethercot, 1997] Ahmed, B. and Nethercot, D. A. (1997). Prediction of initial stiffness and available rotation capacity of major axis composite flush endplate connections. *Journal of Constructional Steel Research*, 41(1):31–60.
- [Alemdar et al., 2000] Alemdar, B. N., White, D. W., and T., L. R. (2000). Frame analysis including 3d slab effects in partially-restrained composite connections. In *Proceedings of the Conference Composite Construction in Steel and Concrete IV*, pages 262–273, Banff, Alberta, Canada.
- [Aribert and Dinga, 2000] Aribert, J. M. and Dinga, O. N. (2000). Modeling and experimental investigation of bolted flush end-plate composite beam-to-column joints. In *Proceedings of the Conference Composite Construction in Steel and Concrete IV*, pages 711–724, Banff, Alberta, Canada.
- [Aribert et al., 1997] Aribert, J. M., Lachal, A., and Dinga, O. N. (1997). Classification and behaviour prediction of beam-to-column composite joints in brace frames. In Bode, H., Ramm, W., Wittek, H., and Schmackpfeffer, H., editors, *Proceedings of the Symposium on Composite Structures*. University of Kaiserslautern.
- [Blodgett, 1966] Blodgett, O. W. (1966). *Design of welded structures*. The James P. Lincoln Arc Welding Foundation, Cleveland, Ohio, USA.
- [Bode, 1996] Bode, H. (1996). Behaviour of composite joints and their influence on semi-continuous composite beams. In *Proceedings of an Engineering Foundation Conference Composite Construction III*, pages 766–777, Irsee, Germany.
- [Bode, 1998] Bode, H. (1998). *Euro-Verbundbau: Konstruktion, Berechnung*. Werner, Düsseldorf, Germany.
- [Bode et al., 1999] Bode, H., Kronenberger, H., and Schmackpfeffer, H. (1999). Teiltragfähige, verformbare Verbindungen im Stahlverbundbau. *Abschlußbericht zum Teilprojekt 2 der DFG-Forschergruppe Verbundbau*. (in German).

- [Bode and Kronenberger, 1997] Bode, H. and Kronenberger, H.-J. (1997). Teiltragfähige, verformbare Verbindungen im Verbundbau. In Bode, H., Ramm, W., Wittek, H., and Schmackpfeffer, H., editors, *Proceedings of the Symposium on Composite Structures*. University of Kaiserslautern. (in German).
- [Bode and Odenbreit, 2000] Bode, H. and Odenbreit, C. (2000). The rotational behaviour and a proposal for the design of composite joints. In *Proceedings of 6th ASCCS Conference, Vol. 2*, pages 697–704, Los Angeles, USA.
- [Bucher et al., 2006] Bucher, C. et al. (2006). *SLang the structural language version 5.1.0*. Institute of Structural Mechanics, Bauhaus-University Weimar.
- [Bursi et al., 2004] Bursi, O. S., Zandonini, R., Salvatore, W., Caramelli, S., and Haller, M. (2004). Seismic behaviour of a 3d full-scale steel-concrete composite moment resisting frame structure. In *Proceedings of the Conference Composite Construction In Steel And Concrete V*, pages 641–652, Berg-en-Dal, Mpumalanga, South Africa.
- [Clemente et al., 2004] Clemente, I., Leon, R. T., Noe, S., and Rassati, G. A. (2004). Interpretation of the experimental behaviour of two semi-rigid composite frames by means of a by-component mechanical model. In *Proceedings of the Conference Composite Construction in Steel and Concrete V*, pages 674–685, Berg-en-Dal, Mpumalanga, South Africa.
- [Crisinel and Carretero, 1996] Crisinel, M. and Carretero, A. (1996). Simple prediction method for moment-rotation properties of composite beam-to-column joints. In *Proceedings of an Engineering Foundation Conference Composite Construction III*, pages 823–835, Irsee, Germany.
- [Crisinel and Kattner, 2000] Crisinel, M. and Kattner, M. (2000). A design method for braced steel frames comprising semi-continuous composite joints. In *Proceedings of the Conference Composite Construction in Steel and Concrete IV*, pages 686–698, Banff, Alberta, Canada.
- [Dorka, 1988] Dorka, U. E. (1988). A contribution to the identification and simplified analysis of structures with hysteresis evolution. TWM Report 88-10, Ruhr-Universität Bochum. (in German).
- [Dorka, 1991] Dorka, U. E. (1991). System analysis by discrete elements. In *Proceedings of the Asian Pacific Conference on Computational Mechanics*, pages 1257–1262, Hong Kong.
- [Dorka, 2009] Dorka, U. E. (2009). Scaled analysis of steel-concrete composite beam-column connections. In *Proceeding of 9th International Conference on Steel Concrete Composite and Hybrid Structures*, Leeds, United Kingdom. (under review).

- [Dorka and Amorntipsakul, 2008] Dorka, U. E. and Amorntipsakul, S. (2008). Macro-elements for composite beam-column connections. In *Proceedings of the Conference Composite Construction in Steel and Concrete VI*, Colorado, USA. in press.
- [Gomez et al., 2008] Gomez, I., Kanvinde, A., Kwan, Y. K., and Grondin, G. (2008). Strength and ductility of welded joints subjected to out-of-plane bending (final report). Technical report, American Institute of Steel Construction, California, USA.
- [Hanswille, 1996] Hanswille, G. (1996). Cracking of concrete mechanical models of the design rules in eurocode 4. In *Proceedings of an Engineering Foundation Conference Composite Construction III*, pages 420–433, Irsee, Germany.
- [Horrigmoe et al., 2007] Horrigmoe, G., Saether, I., Sand, B., and Norut Technology (2007). Validation of nonlinear finite element modelling of reinforced concrete structures attacked by corrosion. Technical Report Background document SB3.11, The European Project Sustainable Bridges – Assessment for Future Traffic Demands and Longer Lives.
- [Huber, 2000] Huber, G. (2000). *Non-linear calculations of composite sections and semi-continuous joints*. Ernst & Sohn, Berlin, Germany.
- [Huber and Tschemmerneegg, 1997] Huber, G. and Tschemmerneegg, F. (1997). Connections – component method. In Bode, H., Ramm, W., Wittek, H., and Schmackpfeffer, H., editors, *Proceedings of the Symposium on Composite Structures*. University of Kaiserslautern. (in German).
- [Kathage and Kindmann, 1996] Kathage, K. and Kindmann, R. (1996). Rotation capacity of partial strength composite connections. In *Proceedings of an Engineering Foundation Conference Composite Construction III*, pages Irsee, Germany, 836–848.
- [Klöppel and Scheer, 1960] Klöppel, K. and Scheer, J. (1960). *Beulwerte ausgesteifter Rechteckplatten Kurventafeln zum direkten Nachweis der Beulsicherheit für verschiedene Steifenanordnungen und Belastungen*. Wilhelm Ernst & Sohn, Berlin, Germany. (in German).
- [Kreller, 1991] Kreller, H. (1991). *Zum nichtlinearen Trag- und Verformungsverhalten von Stahlbeton-stabtragwerken unter Last- und Zwangseinwirkung*, volume Heft 409 des DAfSttb. Ernst & Sohn, Berlin. (in German).
- [Lachal et al., 2004] Lachal, A., Aribert, J. M., and Ciutina, A. (2004). Seismic performance of end-plate moment resisting composite joints. In *Proceedings of the Conference Composite Construction in Steel and Concrete V*, pages 631–640, Berg-en-Dal, Mpumalanga, South Africa.
- [Lam and Fu, 2004] Lam, D. and Fu, F. (2004). Behaviour of semi-rigid composite beam-to-column connections with steel beams and precast hollow core slabs. In *Proceedings of the Conference Composite Construction in Steel and Concrete V*, pages 443–454, Berg-en-Dal, Mpumalanga, South Africa.

- [Leon et al., 1996] Leon, R. T., Hajjar, J. F., and K., S. C. (1996). The effect of composite floor slabs on the behavior of steel moment-resisting frames in the northridge earthquake. In *Proceedings of an Engineering Foundation Conference Composite Construction III*, pages 738–751, Irsee, Germany.
- [Li et al., 1996a] Li, T. Q., Nethercot, D. A., and Choo, B. S. (1996a). Behaviour of flush end-plate composite connections with unbalanced moment and variable shear/moment ratios: part 1: Experimental behaviour. *Journal of Constructional Steel Research*, 38(2):125–164.
- [Li et al., 1996b] Li, T. Q., Nethercot, D. A., and Choo, B. S. (1996b). Behaviour of flush end-plate composite connections with unbalanced moment and variable shear/moment ratios: part 2: Prediction of moment capacity. *Journal of Constructional Steel Research*, 38(2):165–198.
- [Maquoi et al., 2004] Maquoi, R., Jaspart, J. P., and Demonceau, J. F. (2004). Contribution to the design of sway composite frames. In *Proceedings of the Conference Composite Construction in Steel and Concrete V*, pages 653–663, Berg-en-Dal, Mpumalanga, South Africa.
- [Nethercot, 2003] Nethercot, D. A. (2003). *Composite Construction*. Spon Press, London.
- [Nethercot and Ahmed, 1996] Nethercot, D. A. and Ahmed, B. (1996). Numerical modeling of composite connections and composite frames. In *Proceedings of an Engineering Foundation Conference Composite Construction III*, pages 809–822, Irsee, Germany.
- [Nethercot et al., 1996] Nethercot, D. A., Ahmed, B., Li, T. Q., and Xiao, Y. (1996). Design procedures for composite connections. In *Proceedings of an Engineering Foundation Conference Composite Construction III*, pages 794–808, Irsee, Germany.
- [Petersen, 2013] Petersen, C. (2013). *Stahlbau Grundlagen der Berechnung und baulichen Ausbildung von Stahlbauten*. Springer Vieweg, Wiesbaden, Germany. (in German).
- [Picard and Werren, 1984] Picard, A. and Werren, A. (1984). Comportement expérimental et Calcul des assemblages soudés excentriques en flexion. Technical Report Rapport GCI-84-01, Département de Génie civil, Université Laval, Ste-Foy, Québec, Canada.
- [Piyasena et al., 2004] Piyasena, R., Loo, Y., and Fragomeni, S. (2004). Factors influencing spacing and width of cracks in reinforced concrete: New prediction formulae. *Advances in Structural Engineering*, 7(1):49–60.
- [Ramm and Elz, 1996] Ramm, W. and Elz, S. (1996). Behaviour and cracking of slabs as part of composite beams in regions with negative bending moments. In *Proceedings of an Engineering Foundation Conference Composite Construction III*, pages 871–886, Irsee, Germany.

- [Salvatore et al., 2004] Salvatore, W., Braconi, A., and Bursi, O. S. (2004). Component-based models of dissipative partial-strength beam-to-column composite joints. In *Proceedings of the Conference Composite Construction in Steel and Concrete V*, pages 455–466, Berg-en-Dal, Mpumalanga, South Africa.
- [Scheer, 1998] Scheer, J. (1998). *Stahlbauten Erläuterungen zu DIN 18800 Teil 3*. Beuth Verlag, Berlin, Germany. (in German).
- [Shi et al., 1996] Shi, Y. J., Chan, S. L., and Wong, Y. L. (1996). Modeling moment-rotation characteristics for composite end plate connections. In *Proceedings of an Engineering Foundation Conference Composite Construction III*, pages 849–857, Irsee, Germany.
- [Trahair et al., 2008] Trahair, N. S., Bradford, M. A., Nethercot, D. A., and Gardner, L. (2008). *The behaviour and design of steel structures to EC3*. Taylor & Francis, New York, USA.
- [Xiao et al., 1994] Xiao, Y., Choo, B. S., and Nethercot, D. A. (1994). Composite connection in steel and concrete. i. experimental behaviour of composite beam-column connections. *Journal of Constructional Steel Research*, 31:3–30.